



SDI12-12-UDC-P6R Information

www.helsener.com

Part Number SDI12-12-UDC-P6R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 12W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI12-12-UDC-P6R Specifications

Manufacturer Part Number SDI12-12-UDC-P6R Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Reckage - Series SDI12-UD Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI12-UD Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Manufacturer Part Number	SDI12-12-UDC-P6R
Package - Series SDI12-UD Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Manufacturer	CUI Inc.
Package - Series SDI12-UD Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI12-UDRegion UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1APower (Watts)12WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $12V$ Current - Output (Max) $1A$ Power (Watts) $12W$ No Load Power Consumption 100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension $2.95^{\circ\circ}$ L $x 1.89^{\circ\circ}$ W $x 1.18^{\circ\circ}$ H (75.0mm $x 48.0\text{mm}$ $x 30.0\text{mm}$)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Series	SDI12-UD
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) $1A$ Power (Watts) 12W No Load Power Consumption 100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 2.95° L x 1.89° W x 1.18° H (75.0mm x 48.0mm x 30.0mm)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 12V 12V 12V 12W 12W 10mW (Max) Positive Center 100mW (Max) Positive Center 100mW (Max) 100mW (Max)	Input Type	Cord
Current - Output (Max) Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 12W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Voltage - Output	12V
No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Current - Output (Max)	1A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug R/A, 2.5 mm I.D. $x 5.5$ mm O.D. $x 9.5$ mmSize / Dimension 2.95 " L $x 1.89$ " W $x 1.18$ " H (75.0 mm $x 48.0$ mm $x 30.0$ mm)	Power (Watts)	12W
Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	No Load Power Consumption	100mW (Max)
Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $2.95^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 1.18^{\circ}\text{H} (75.0\text{mm} \times 48.0\text{mm} \times 30.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.95" L x 1.89" W x 1.18" H (75.0mm x 48.0mm x 30.0mm)
		Report errors?

SDI12-12-UDC-P6R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI12-12-UDC-P6R Payment Methods



















SDI12-12-UDC-P6R Shipping Methods













If you have any question about SDI12-12-UDC-P6R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com