

## SDI18-12-U-P5 Information

ww.helsener.com

Part Number SDI18-12-U-P5

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

AC/DC DESKTOP ADAPTER 12V 18W **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SDI18-12-U-P5 Specifications

Manufacturer Part Number         SDI18-12-U-P5           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI18-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.6A           Power (Watts)         19W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI18-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.6A           Power (Watts)         19W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Manufacturer Part Number	SDI18-12-U-P5
Package-SeriesSDI18-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Manufacturer	CUI Inc.
Package         -           Series         SDI18-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.6A           Power (Watts)         19W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSD118-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.6A  Power (Watts) 19W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Series	SDI18-U
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.6A  Power (Watts) 19W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $12\text{V}$ Current - Output (Max) $1.6\text{A}$ Power (Watts) $19\text{W}$ No Load Power Consumption $100\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm}$ I.D. x $5.5\text{mm}$ O.D. x $9.5\text{mm}$ Size / Dimension $3.94^{\circ}\text{L}$ x $1.97^{\circ}$ W x $1.30^{\circ}$ H ( $100.0\text{mm}$ x $50.0\text{mm}$ x $33.0\text{mm}$ )	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  1.6A  Power (Watts)  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Current - Output (Max)  Power (Watts)  Power (Watts)  Positive Center  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  1.6A  Power (Watts)  19W  No Load Power Consumption  100mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  19W  No Load Power Consumption  100mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Voltage - Output	12V
No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Current - Output (Max)	1.6A
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Power (Watts)	19W
Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}$ C ~ $40^{\circ}$ C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $3.94^{\circ}$ L x $1.97^{\circ}$ W x $1.30^{\circ}$ H ( $100.0$ mm x $50.0$ mm x $33.0$ mm)	No Load Power Consumption	100mW (Max)
Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $3.94^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.30^{\circ}\text{H} (100.0\text{mm} \times 50.0\text{mm} \times 33.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $3.94^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.30^{\circ}\text{H} (100.0\text{mm} \times 50.0\text{mm} \times 33.0\text{mm})$	Applications	ITE (Commercial)
Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)
		Report errors

#### SDI18-12-U-P5 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SDI18-12-U-P5 Payment Methods



















### SDI18-12-U-P5 Shipping Methods













If you have any question about SDI18-12-U-P5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com