

#### SDI18-12-U-P6 Information

ww.helsener.com

Part Number SDI18-12-U-P6

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 12V 18W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SDI18-12-U-P6 Specifications

Manufacturer Part Number         SDI18-12-U-P6           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI18-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.6A           Power (Watts)         19W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI18-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.6A           Power (Watts)         19W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Manufacturer Part Number	SDI18-12-U-P6
Package-SeriesSDI18-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Manufacturer	CUI Inc.
Package-SeriesSDI18-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI18-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.6A  Power (Watts) 19W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Series	SDI18-U
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.6A  Power (Watts) 19W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Region Utilized	International
Voltage - Input  90 ~ 264 VAC  Voltage - Output  12V  Current - Output (Max)  1.6A  Power (Watts)  19W  No Load Power Consumption  100mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Form	Desktop (Class I)
Voltage - Output (Max)  Current - Output (Max)  1.6A  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  12V  1.6A  19W  100mW (Max)  Positive Center  100mW (Max)  Positive Center  100mW (Max)  Positive Center  100mW (Max)  Positive Center  11E (Commercial)  11E (Commercial)  12V  100mW (Max)  110mW (Max)	Input Type	Cord (Sold Separately)
Current - Output (Max)  1.6A  Power (Watts)  19W  No Load Power Consumption  100mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  19W  No Load Power Consumption  100mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Voltage - Output	12V
No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Current - Output (Max)	1.6A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}$ C ~ $40^{\circ}$ COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $3.94$ " L x $1.97$ " W x $1.30$ " H ( $100.0$ mm x $50.0$ mm x $33.0$ mm)	Power (Watts)	19W
Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $3.94^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.30^{\circ}\text{H} (100.0\text{mm} \times 50.0\text{mm} \times 33.0\text{mm})$	No Load Power Consumption	100mW (Max)
Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $3.94^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.30^{\circ}\text{H} (100.0\text{mm} \times 50.0\text{mm} \times 33.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $3.94^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.30^{\circ}\text{H} (100.0\text{mm} \times 50.0\text{mm} \times 33.0\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.94" L x 1.97" W x 1.30" H (100.0mm x 50.0mm x 33.0mm)
•		Report errors

#### SDI18-12-U-P6 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SDI18-12-U-P6 Payment Methods



















# SDI18-12-U-P6 Shipping Methods













If you have any question about SDI18-12-U-P6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com