



SDI30-12-U2-P6R Information

Part Number SDI30-12-U2-P6R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 30W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI30-12-U2-P6R Specifications

Manufacturer Part Number SDI30-12-U2-P6R Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Reckage - Series SDI30-U Region Utilized Europe Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI30-U Region Utilized Europe Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Manufacturer Part Number	SDI30-12-U2-P6R
Package - Series SDI30-U Region Utilized Europe Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Manufacturer	CUI Inc.
Package - Series SDI30-U Region Utilized Europe Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSD130-URegion UtilizedEuropeFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)		AC DC Desktop, Wall Adapters
Region UtilizedEuropeFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2.5APower (Watts)30WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Series	SDI30-U
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension 4.37 " L $x 2.05$ " W $x 1.27$ " H (111.0mm x 52.0mm x 32.3mm)	Region Utilized	Europe
Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2.5A Power (Watts) No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 2.5A Power (Watts) No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Input Type	Cord
Current - Output (Max) 2.5A Power (Watts) 30W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption 75mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Voltage - Output	12V
No Load Power Consumption 75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 4.37 " L x 2.05 " W x 1.27 " H (111.0mm x 52.0mm x 32.3mm)	Current - Output (Max)	2.5A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 4.37 " L x 2.05 " W x 1.27 " H (111.0 mm x 52.0 mm x 32.3 mm)	Power (Watts)	30W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.37^{\circ}\text{L} \times 2.05^{\circ}\text{W} \times 1.27^{\circ}\text{H} (111.0 \text{mm} \times 52.0 \text{mm} \times 32.3 \text{mm})$	No Load Power Consumption	75mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.37^{\circ}\text{L} \times 2.05^{\circ}\text{W} \times 1.27^{\circ}\text{H} (111.0 \text{mm} \times 52.0 \text{mm} \times 32.3 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.37^{\circ}\text{L} \times 2.05^{\circ}\text{W} \times 1.27^{\circ}\text{H} (111.0\text{mm} \times 52.0\text{mm} \times 32.3\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Efficiency	Level VI
Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)
		Report errors?

SDI30-12-U2-P6R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI30-12-U2-P6R Payment Methods



















SDI30-12-U2-P6R Shipping Methods













If you have any question about SDI30-12-U2-P6R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com