

SDI40-12-UC-P6

SDI40-12-UC-P6 Information

1	Part Number Manufacture Category Description Package	Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC DESKTOP ADAPTER 12V 40W - For the pricing/inventory/lead time, please contact	
For	r Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SDI40-12-UC-P6 Specifications

Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC DC Desktop, Wall Adapters Package - Series SDI40-U Region Utilized North America Power Supplies - External/Internal (Off-Board) Desktop, Wall Adapters Form SDI40-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm			
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package Package Series Softer Series Softer Power Outplitzed North America Form Desktop (Class I) Input Type Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 3A Power (Watts) No Load Power Consumption 75mW (Max) Polarization Applications Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension	Manufacturer Part Number	SDI40-12-UC-P6	
AC DC bestrop, Wall AdaptersPackage-SeriesSDI40-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Manufacturer	CUI Inc.	
Package-SeriesSDI40-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SDI40-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 3A Power (Watts) 36W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dinension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)		AC DC Desktop, Wall Adapters	
Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output90 ~ 264 VACVoltage - Output (Max)3APower (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSte / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Package	-	
FormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COperating Temperature0°C ~ 40°CSter / DimensionBartel Plug, 2.5mm I.D. x 9.5mm O.D. x 9.5mm	Series	SDI40-U	
Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Region Utilized	North America	
Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Form	Desktop (Class I)	
Voltage - Output12VCurrent - Output (Max)3APower (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Input Type	Cord	
Current - Output (Max)3APower (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Voltage - Input	90 ~ 264 VAC	
Power (Watts)36WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Voltage - Output	12V	
No Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Current - Output (Max)	3A	
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Power (Watts)	36W	
ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	No Load Power Consumption	75mW (Max)	
EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Polarization	Positive Center	
Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Applications	ITE (Commercial)	
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Efficiency	Level VI	
Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Operating Temperature	$0^{\circ}C \sim 40^{\circ}C$	
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	
Report errors?	Size / Dimension	4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	
			Report errors?

SDI40-12-UC-P6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI40-12-UC-P6 Payment Methods



SDI40-12-UC-P6 Shipping Methods



If you have any question about SDI40-12-UC-P6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com