

# SDI40-15-U-P5 Information

Part Number SDI40-15-U-P5

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 15V 40W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SDI40-15-U-P5 Specifications

Manufacturer Part Number         SDI40-15-U-P5           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI40-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         2.7A           Power (Watts)         41W           No Load Power Consumption         75mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)    Report errors?			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI40-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         2.7A           Power (Watts)         41W           No Load Power Consumption         75mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Manufacturer Part Number	SDI40-15-U-P5	
Package         -           Series         SDI40-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         2.7A           Power (Watts)         41W           No Load Power Consumption         75mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Manufacturer	CUI Inc.	
Package         -           Series         SDI40-U           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         2.7A           Power (Watts)         41W           No Load Power Consumption         75mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Category	Power Supplies - External/Internal (Off-Board)	
SeriesSDI40-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)2.7APower (Watts)41WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)		AC DC Desktop, Wall Adapters	
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 2.7A Power (Watts) 41W No Load Power Consumption 75mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Package	-	
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 2.7A  Power (Watts) 41W  No Load Power Consumption 75mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Series	SDI40-U	
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 2.7A  Power (Watts) 41W  No Load Power Consumption 75mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Region Utilized	International	
Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)2.7APower (Watts)41WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Form	Desktop (Class I)	
Voltage - Output (Max) 2.7A  Power (Watts) 41W  No Load Power Consumption 75mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Input Type	Cord (Sold Separately)	
Current - Output (Max)  2.7A  Power (Watts)  41W  No Load Power Consumption  75mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Voltage - Input	90 ~ 264 VAC	
Power (Watts)  A1W  No Load Power Consumption  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  A37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Voltage - Output	15V	
No Load Power Consumption $75 \text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm}$ I.D. $x$ 5.5mm O.D. $x$ 9.5mmSize / Dimension $4.37$ " L $x$ 2.05" W $x$ 1.27" H (111.0mm $x$ 52.0mm $x$ 32.3mm)	Current - Output (Max)	2.7A	
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Power (Watts)	41W	
Applications ITE (Commercial)  Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.37^{\circ}\text{L} \times 2.05^{\circ}\text{W} \times 1.27^{\circ}\text{H} (111.0 \text{mm} \times 52.0 \text{mm} \times 32.3 \text{mm})$	No Load Power Consumption	75mW (Max)	
Efficiency Level VI  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.37^{\circ}\text{L} \times 2.05^{\circ}\text{W} \times 1.27^{\circ}\text{H} (111.0\text{mm} \times 52.0\text{mm} \times 32.3\text{mm})$	Polarization	Positive Center	
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.37^{\circ}\text{L} \times 2.05^{\circ}\text{W} \times 1.27^{\circ}\text{H} (111.0\text{mm} \times 52.0\text{mm} \times 32.3\text{mm})$	Applications	ITE (Commercial)	
Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Efficiency	Level VI	
Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Operating Temperature	0°C ~ 40°C	
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm	
Report errors?	Size / Dimension	4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	
		Report errors	s?

#### SDI40-15-U-P5 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SDI40-15-U-P5 Payment Methods



















# SDI40-15-U-P5 Shipping Methods













If you have any question about SDI40-15-U-P5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com