

# SDI40-19-UC-P6

### **SDI40-19-UC-P6 Information**

ww.itelsener.com	Part Number Manufacturer Category Description Package	SDI40-19-UC-P6 CUI Inc. Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC DESKTOP ADAPTER 19V 40W - For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **SDI40-19-UC-P6 Specifications**

Manufacturer Part Number SDI40-19-UC-P6   Manufacturer CUI Inc.   Category Power Supplies - External/Internal (Off-Board)   AC DC Desktop, Wall Adapters AC DC Desktop, Wall Adapters   Package -   Series SDI40-U   Region Utilized North America   Form Desktop (Class I)   Input Type Cord   Voltage - Input 90 ~ 264 VAC   Voltage - Output 19V   Current - Output (Max) 2.1A   Power (Watts) 40W   No Load Power Consumption 75mW (Max)   Polarization Positive Center   Applications ITE (Commercial)   Efficiency Level VI   Operating Temperature 0°C ~ 40°C   Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm   Siz / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)			
Category Power Supplies - External/Internal (Off-Board)   AC DC Desktop, Wall Adapters   Package -   Series SDI40-U   Region Utilized North America   Form Desktop (Class I)   Input Type Cord   Voltage - Input 90 ~ 264 VAC   Voltage - Output (Max) 90 ~ 264 VAC   Current - Output (Max) 2.1A   Power (Watts) 40W   No Load Power Consumption 7smW (Max)   Polarization Positive Center   Applications ITE (Commercial)   Efficiency Level VI   Operating Temperature 0°C ~ 40°C   Output Connector Bartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Manufacturer Part Number	SD140-19-UC-P6	
AC DC bestop, Wall AdaptersPackage-SeriesSDI40-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)2.1APower (Watts)40WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0° C ~ 40°COutput ConnectorBartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm (S2.3mm)Size / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Manufacturer	CUI Inc.	
Package-SeriesSDI40-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output90 ~ 264 VACVoltage - Output (Max)2.1APower (Watts)40WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBartel Plug. 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SDI40-U   Region Utilized North America   Form Desktop (Class I)   Input Type Cord   Voltage - Input 90 ~ 264 VAC   Voltage - Output 19V   Current - Output (Max) 2.1A   Power (Watts) 40W   No Load Power Consumption 75mW (Max)   Polarization Positive Center   Applications ITE (Commercial)   Efficiency Level VI   Operating Temperature 0°C ~ 40°C   Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm X32.3mm)		AC DC Desktop, Wall Adapters	
Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)2.1APower (Watts)40WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Package	-	
FormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)2.1APower (Watts)40WNo Load Power Consumption75mV (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.31" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Series	SDI40-U	
Input Type Cord   Voltage - Input 90 ~ 264 VAC   Voltage - Output 19V   Current - Output (Max) 19V   Power (Watts) 2.1A   No Load Power Consumption 75mV (Max)   Polarization 75mV (Max)   Polarization Positive Center   Applications ITE (Commercial)   Efficiency Level VI   Operating Temperature 0°C ~ 40°C   Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Region Utilized	North America	
Voltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)2.1APower (Watts)40WNo Load Power Consumption75mV (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Form	Desktop (Class I)	
Voltage - Output19VCurrent - Output (Max)2.1APower (Watts)40WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Input Type	Cord	
Current - Output (Max)2.1APower (Watts)40WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Voltage - Input	90 ~ 264 VAC	
Power (Watts)40WNo Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Voltage - Output	19V	
No Load Power Consumption75mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Current - Output (Max)	2.1A	
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Power (Watts)	40W	
ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	No Load Power Consumption	75mW (Max)	
EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Polarization	Positive Center	
Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Applications	ITE (Commercial)	
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Efficiency	Level VI	
Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Operating Temperature	$0^{\circ}$ C ~ $40^{\circ}$ C	
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	
Report errors?	Size / Dimension	4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	
			Report errors?

#### **SDI40-19-UC-P6** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### SDI40-19-UC-P6 Payment Methods



## SDI40-19-UC-P6 Shipping Methods



If you have any question about SDI40-19-UC-P6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com