



SDI40-24-UC-P6R Information

Part Number SDI40-24-UC-P6R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 40W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI40-24-UC-P6R Specifications

ManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesSDI40-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)1.7APower (Watts)41WNo Load Power Consumption75mW (Max)PolarizationPositive Center		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI40-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.7A Power (Watts) 41W No Load Power Consumption 75mW (Max) Polarization Positive Center	Manufacturer Part Number	SDI40-24-UC-P6R
AC DC Desktop, Wall Adapters Package - Series SDI40-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.7A Power (Watts) 41W No Load Power Consumption 75mW (Max) Polarization Positive Center	Manufacturer	CUI Inc.
Package - SDI40-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.7A Power (Watts) 41W No Load Power Consumption 75mW (Max) Polarization Positive Center	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI40-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)1.7APower (Watts)41WNo Load Power Consumption75mW (Max)PolarizationPositive Center		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)1.7APower (Watts)41WNo Load Power Consumption75mW (Max)PolarizationPositive Center	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.7A Power (Watts) 41W No Load Power Consumption 75mW (Max) Polarization Positive Center	Series	SDI40-U
Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.7A Power (Watts) 41W No Load Power Consumption 75mW (Max) Polarization Positive Center	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 1.7A Power (Watts) No Load Power Consumption Polarization Positive Center	Form	Desktop (Class I)
Voltage - Output 24V Current - Output (Max) 1.7A Power (Watts) 41W No Load Power Consumption 75mW (Max) Polarization Positive Center	Input Type	Cord
Current - Output (Max) Power (Watts) No Load Power Consumption Polarization 1.7A 41W 75mW (Max) Positive Center	Voltage - Input	90 ~ 264 VAC
Power (Watts) 41W No Load Power Consumption 75mW (Max) Polarization Positive Center	Voltage - Output	24V
No Load Power Consumption 75mW (Max) Polarization Positive Center	Current - Output (Max)	1.7A
Polarization Positive Center	Power (Watts)	41W
	No Load Power Consumption	75mW (Max)
A TO STATE OF THE CO. S	Polarization	Positive Center
Applications ITE (Commercial)	Applications	ITE (Commercial)
Efficiency Level VI	Efficiency	Level VI
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Size / Dimension 4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)	Size / Dimension	4.37" L x 2.05" W x 1.27" H (111.0mm x 52.0mm x 32.3mm)
Report errors		Report errors?

SDI40-24-UC-P6R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI40-24-UC-P6R Payment Methods



















SDI40-24-UC-P6R Shipping Methods













If you have any question about SDI40-24-UC-P6R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com