

SDI50-15-U-P6R Information



For Reference Only

Part Number SDI50-15-U-P6R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 15V 50W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI50-15-U-P6R Specifications

Manufacturer Part Number SDI50-15-U-P6R Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI50-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 3.34A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI50-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 3.34A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer Part Number	SDI50-15-U-P6R
AC DC Desktop, Wall Adapters Package Series SDI50-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 3.34A Power (Watts) SoW No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension AC DC Desktop, Wall Adapters SDI50-U International AC DC Desktop, Wall Adapters Applicational International In	Manufacturer	CUI Inc.
Package - Series SDI50-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 3.34A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSD150-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)3.34APower (Watts)50WNo Load Power Consumption150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 3.34A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 3.34A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Series	SDI50-U
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 3.34A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 15V Current - Output (Max) 3.34A Power (Watts) 50W No Load Power Consumption 150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0 \text{mm} \times 53.0 \text{mm} \times 38.0 \text{mm})$	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 3.34A Power (Watts) No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 15V 3.34A Power (Watts) FOW Contest Cont	Input Type	Cord (Sold Separately)
Current - Output (Max) 3.34A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Output	15V
No Load Power Consumption 150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 4.53 " L x 2.09 " W x 1.50 " H (115.0mm x 53.0mm x 38.0mm)	Current - Output (Max)	3.34A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0 \text{mm} \times 53.0 \text{mm} \times 38.0 \text{mm})$	Power (Watts)	50W
Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53° L x 2.09° W x 1.50° H (115.0mm x 53.0 mm x 38.0 mm)	No Load Power Consumption	150mW (Max)
Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)
		Report errors?

SDI50-15-U-P6R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI50-15-U-P6R Payment Methods


































If you have any question about SDI50-15-U-P6R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com