

SDI50-19-UC-P6 Information

www.horsyrer.com

For Reference Only

Part Number SDI50-19-UC-P6

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 19V 50W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI50-19-UC-P6 Specifications

Manufacturer Part Number SDI50-19-UC-P6 Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series SDI50-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI50-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer Part Number	SDI50-19-UC-P6
Package - Series SDI50-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer	CUI Inc.
Package - Series SDI50-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI50-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)2.64APower (Watts)50WNo Load Power Consumption150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 19V Current - Output (Max) 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53° L x 2.09° W x 1.50° H (115.0mm x $53.0mm$ x $38.0mm)$	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Series	SDI50-U
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 19V Current - Output (Max) 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H}$ (115.0mm $\times 53.0\text{mm} \times 38.0\text{mm}$)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 2.64A Power (Watts) No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 90 ~ 264 VAC 19V 19V 10V 10V 10V 10V 10V 10V	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 2.64A Power (Watts) No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 19V 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max) Positive Center Commercial) Level VI, CoC Tier 2 Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Input Type	Cord
Current - Output (Max) 2.64A Power (Watts) 50W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $50W$ No Load Power Consumption $150mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, $2.5mm$ I.D. x $5.5mm$ O.D. x $9.5mm$ Size / Dimension 4.53 " L x 2.09 " W x 1.50 " H ($115.0mm$ x $53.0mm$ x $38.0mm$)	Voltage - Output	19V
No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Current - Output (Max)	2.64A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0 \text{mm} \times 53.0 \text{mm} \times 38.0 \text{mm})$	Power (Watts)	50W
Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53''$ L x $2.09''$ W x $1.50''$ H (115.0mm x 53.0 mm x 38.0 mm)	No Load Power Consumption	150mW (Max)
Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)
		Report errors?

SDI50-19-UC-P6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI50-19-UC-P6 Payment Methods



















SDI50-19-UC-P6 Shipping Methods













If you have any question about SDI50-19-UC-P6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com