



### SDI65-18-UC-P5R Information

Heisener.com

Part Number SDI65-18-UC-P5R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **SDI65-18-UC-P5R Specifications**

Manufacturer Part Number         SDI65-18-UC-P5R           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI65-U           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         18V           Current - Output (Max)         3.62A           Power (Watts)         65W           No Load Power Consumption         210mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI65-U           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         18V           Current - Output (Max)         3.62A           Power (Watts)         65W           No Load Power Consumption         210mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer Part Number	SDI65-18-UC-P5R
Package         -           Series         SDI65-U           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         18V           Current - Output (Max)         3.62A           Power (Watts)         65W           No Load Power Consumption         210mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer	CUI Inc.
Package         -           Series         SDI65-U           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         18V           Current - Output (Max)         3.62A           Power (Watts)         65W           No Load Power Consumption         210mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI65-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output18VCurrent - Output (Max)3.62APower (Watts)65WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $18V$ Current - Output (Max) $3.62A$ Power (Watts) $65W$ No Load Power Consumption $210\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm}$ I.D. $x$ $5.5\text{mm}$ O.D. $x$ $9.5\text{mm}$ Size / Dimension $4.53^{\circ}$ L $x$ $2.09^{\circ}$ W $x$ $1.50^{\circ}$ H (115.0mm $x$ $53.0\text{mm}$ $x$ $38.0\text{mm}$ )	Package	-
Form Desktop (Class I) Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 18V  Current - Output (Max) 3.62A  Power (Watts) 65W  No Load Power Consumption 210mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Series	SDI65-U
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $18\text{V}$ Current - Output (Max) $3.62\text{A}$ Power (Watts) $65\text{W}$ No Load Power Consumption $210\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm}$ I.D. $x$ 5.5mm O.D. $x$ 9.5mmSize / Dimension $4.53^{\circ}\text{L}$ x $2.09^{\circ}$ W x $1.50^{\circ}$ H ( $115.0\text{mm}$ x $53.0\text{mm}$ x $38.0\text{mm}$ )	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  18V  Current - Output (Max)  3.62A  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  90 ~ 264 VAC  18V  10 Current - Output (Max)  11 Current - Output (Max)  12 Current - Output (Max)  13 Current - Output (Max)  14.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  3.62A  Power (Watts)  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  18V  3.62A  65W  No Load Power Consumption  Positive Center  Commercial)  Level VI, CoC Tier 2  O°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Input Type	Cord
Current - Output (Max)  3.62A  Power (Watts)  65W  No Load Power Consumption  210mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  65W  No Load Power Consumption  210mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Output	18V
No Load Power Consumption 210mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Current - Output (Max)	3.62A
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0 \text{mm} \times 53.0 \text{mm} \times 38.0 \text{mm})$	Power (Watts)	65W
Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}$ C ~ $40^{\circ}$ C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.53^{\circ}$ L x $2.09^{\circ}$ W x $1.50^{\circ}$ H (115.0mm x $53.0$ mm x $38.0$ mm)	No Load Power Consumption	210mW (Max)
Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)
		Report errors?

#### SDI65-18-UC-P5R Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## SDI65-18-UC-P5R Payment Methods



















# SDI65-18-UC-P5R Shipping Methods













If you have any question about SDI65-18-UC-P5R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com