



### SDI65-19-UD-P5R Information



For Reference Only

Part Number SDI65-19-UD-P5R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 19V 65W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SDI65-19-UD-P5R Specifications

Manufacturer Part Number         SDI65-19-UD-P5R           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         SDI65-UD           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         19V           Current - Output (Max)         3.43A           Power (Watts)         65W           No Load Power Consumption         210mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         SDI65-UD           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         19V           Current - Output (Max)         3.43A           Power (Watts)         65W           No Load Power Consumption         210mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer Part Number	SDI65-19-UD-P5R
Package - Series SDI65-UD  Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 19V  Current - Output (Max) 3.43A  Power (Watts) 65W  No Load Power Consumption 210mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension x 3000 March 115.0mm x 53.0mm x 38.0mm)	Manufacturer	CUI Inc.
Package         -           Series         SDI65-UD           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         19V           Current - Output (Max)         3.43A           Power (Watts)         65W           No Load Power Consumption         210mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI65-UDRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)3.43APower (Watts)65WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Series	SDI65-UD
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $19\text{V}$ Current - Output (Max) $3.43\text{A}$ Power (Watts) $65\text{W}$ No Load Power Consumption $210\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $2.1\text{mm}$ I.D. $\times 5.5\text{mm}$ O.D. $\times 9.5\text{mm}$ Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H}$ ( $115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm}$ )	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $19\text{V}$ Current - Output (Max) $3.43\text{A}$ Power (Watts) $65\text{W}$ No Load Power Consumption $210\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $2.1\text{mm}$ I.D. x $5.5\text{mm}$ O.D. x $9.5\text{mm}$ Size / Dimension $4.53^{\circ}\text{L}$ x $2.09^{\circ}$ W x $1.50^{\circ}$ H ( $115.0\text{mm}$ x $53.0\text{mm}$ x $38.0\text{mm}$ )	Form	Desktop (Class II)
Voltage - Output  Current - Output (Max)  3.43A  Power (Watts)  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  3.43A  Power (Watts)  65W  No Load Power Consumption  210mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $65W$ No Load Power Consumption $210mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, $2.1mm$ I.D. $x$ $5.5mm$ O.D. $x$ $9.5mm$ Size / Dimension $4.53$ " L $x$ $2.09$ " W $x$ $1.50$ " H ( $115.0mm$ $x$ $53.0mm$ $x$ $38.0mm$ )	Voltage - Output	19V
No Load Power Consumption 210mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Current - Output (Max)	3.43A
Polarization Positive Center  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Power (Watts)	65W
Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}$ C ~ $40^{\circ}$ C  Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.53^{\circ}$ L x $2.09^{\circ}$ W x $1.50^{\circ}$ H (115.0mm x $53.0$ mm x $38.0$ mm)	No Load Power Consumption	210mW (Max)
Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)
		Report errors?

#### SDI65-19-UD-P5R Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SDI65-19-UD-P5R Payment Methods



















## SDI65-19-UD-P5R Shipping Methods













If you have any question about SDI65-19-UD-P5R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com