



SDI65-19-UDC-P5 Information



For Reference Only

Part Number SDI65-19-UDC-P5

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 19V 65W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI65-19-UDC-P5 Specifications

Manufacturer Part Number SDI65-19-UDC-P5 Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series SDI65-UD Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI65-UD Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer Part Number	SDI65-19-UDC-P5
Package-SeriesSDI65-UDRegion UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)3.43APower (Watts)65WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer	CUI Inc.
Package - Series SDI65-UD Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI65-UDRegion UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)3.43APower (Watts)65WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Series	SDI65-UD
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 4.53°L x 2.09° W x 1.50° H (115.0mm x 53.0mm x 38.0mm)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 3.43A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 90 ~ 264 VAC 19V 19V 10V 10V 10V 10V 10V 10V	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 3.43A Power (Watts) No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Current - Output (Max) Power (Watts) For in the properties of t	Input Type	Cord
Current - Output (Max) 3.43A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption 210mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Output	19V
No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Current - Output (Max)	3.43A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0 \text{mm} \times 53.0 \text{mm} \times 38.0 \text{mm})$	Power (Watts)	65W
Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53° L x 2.09° W x 1.50° H (115.0mm x 53.0 mm x 38.0 mm)	No Load Power Consumption	210mW (Max)
Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)
		Report errors?

SDI65-19-UDC-P5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI65-19-UDC-P5 Payment Methods





















SDI65-19-UDC-P5 Shipping Methods













If you have any question about SDI65-19-UDC-P5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com