

SDI90-12-U-P5 Information



For Reference Only

Part Number SDI90-12-U-P5

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 90W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI90-12-U-P5 Specifications

Manufacturer Part Number SDI90-12-U-P5 Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI90-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI90-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Manufacturer Part Number	SDI90-12-U-P5
Package-SeriesSDI90-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)7APower (Watts)84WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Manufacturer	CUI Inc.
Package - Series SDI90-U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI90-URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)7APower (Watts)84WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Series	SDI90-U
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Region Utilized	International
Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)7APower (Watts)84WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12	Input Type	Cord (Sold Separately)
Current - Output (Max) Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Voltage - Output	12V
No Load Power Consumption 210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 5.94 " L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Current - Output (Max)	7A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Power (Watts)	84W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	No Load Power Consumption	210mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.94^{\circ}\text{L} \times 2.52^{\circ}\text{W} \times 1.42^{\circ}\text{H} (151.0\text{mm} \times 64.0\text{mm} \times 36.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.94^{\circ}\text{L} \times 2.52^{\circ}\text{W} \times 1.42^{\circ}\text{H} (151.0\text{mm} \times 64.0\text{mm} \times 36.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Efficiency	Level VI
Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)
		Report errors?

SDI90-12-U-P5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI90-12-U-P5 Payment Methods



















SDI90-12-U-P5 Shipping Methods













If you have any question about SDI90-12-U-P5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com