



SDI90-19-UC-P5R Information



For Reference Only

Part Number SDI90-19-UC-P5R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI90-19-UC-P5R Specifications

Manufacturer Part Number SDI90-19-UC-P5R Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Reckage - Series SDI90-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI90-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Manufacturer Part Number	SDI90-19-UC-P5R
Package - Series SDI90-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Manufacturer	CUI Inc.
Package - Series SDI90-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSD190-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)4.74APower (Watts)90WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Series	SDI90-U
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 19V Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption 210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension 5.94°L x 2.52° W x 1.42° H (151.0mm x 64.0mm x 36.0mm)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.74A Power (Watts) No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Input Type	Cord
Current - Output (Max) 4.74A Power (Watts) 90W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 90W No Load Power Consumption 210mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Voltage - Output	19V
No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Current - Output (Max)	4.74A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Power (Watts)	90W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94° L x 2.52° W x 1.42° H (151.0mm x 64.0 mm x 36.0 mm)	No Load Power Consumption	210mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.94^{\circ}\text{L} \times 2.52^{\circ}\text{W} \times 1.42^{\circ}\text{H} (151.0 \text{mm} \times 64.0 \text{mm} \times 36.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Efficiency	Level VI
Size / Dimension 5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	5.94" L x 2.52" W x 1.42" H (151.0mm x 64.0mm x 36.0mm)
		Report errors?

SDI90-19-UC-P5R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI90-19-UC-P5R Payment Methods



















SDI90-19-UC-P5R Shipping Methods













If you have any question about SDI90-19-UC-P5R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com