

SDR-30 Information



For Reference Only

Part Number SDR-30 **Manufacturer** CUI Inc.

Category Connectors, Interconnects Circular Connectors

Description CONN DIN 3PIN R/ANGLE PLUG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDR-30 Specifications

Manufacturer Part Number SDR-30 Manufacturer CUI Inc. Category Connectors, Interconnects Package - Series SDR Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert DIN Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating IA		
CategoryConnectors, InterconnectsPackage-SeriesSDRConnector TypePlug, Male PinsNumber of Positions3Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated100VACCurrent Rating1A	Manufacturer Part Number	SDR-30
Package-SeriesSDRConnector TypePlug, Male PinsNumber of Positions3Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated100VACCurrent Rating1A	Manufacturer	CUI Inc.
Package-SeriesSDRConnector TypePlug, Male PinsNumber of Positions3Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated100VACCurrent Rating1A	Category	Connectors, Interconnects
SeriesSDRConnector TypePlug, Male PinsNumber of Positions3Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated100VACCurrent Rating1A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions3Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated100VACCurrent Rating1A	Package	-
Number of Positions3Shell Size - InsertDINShell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated100VACCurrent Rating1A	Series	SDR
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating 1A	Number of Positions	3
Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated100VACCurrent Rating1A	Shell Size - Insert	DIN
Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating 1A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating 1A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating 1A	Termination	Solder
Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating 1A	Fastening Type	Push-Pull
Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating 1A	Orientation	Keyed
Contact Finish Nickel Features - Voltage - Rated 100VAC Current Rating 1A	Ingress Protection	-
Features - Voltage - Rated 100VAC Current Rating 1A	Shell Material, Finish	Polybutylene Terephthalate (PBT)
Voltage - Rated 100VAC Current Rating 1A	Contact Finish	Nickel
Current Rating 1A	Features	-
	Voltage - Rated	100VAC
Report errors?	Current Rating	1A
		Report errors?

SDR-30 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDR-30 Payment Methods

































If you have any question about SDR-30, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com