



SDR1030-680M Information



For Reference Only

Part Number SDR1030-680M Manufacturer Bourns Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 68UH 820MA 360 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDR1030-680M Specifications

ManufacturerBourns Inc.CategoryInductors, Coils, ChokesFixed InductorsPackageNonstandardSeriesSDR1030TypeWirewoundMaterial - CoreFerriteInductance68μHTolerance±20%Current Rating820mACurrent - Saturation900mAShieldingUnshieldedDC Resistance (DCR)360 mOhm MaxQ @ Freq12 @ 2.52MHzFrequency - Self Resonant12.2MHz	
Fixed Inductors Package Nonstandard Series SDR1030 Type Wirewound Material - Core Ferrite Inductance 68μH Tolerance ±20% Current Rating 820mA Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Package Nonstandard Series SDR1030 Type Wirewound Material - Core Ferrite Inductance 68μH Tolerance ±20% Current Rating 820mA Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Series SDR1030 Type Wirewound Material - Core Ferrite Inductance 68μH Tolerance ±20% Current Rating 820mA Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Type Wirewound Material - Core Ferrite Inductance 68μH Tolerance ±20% Current Rating 820mA Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Material - Core Ferrite Inductance 68μH Tolerance ±20% Current Rating 820mA Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Inductance 68μH Tolerance ±20% Current Rating 820mA Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Tolerance ±20% Current Rating 820mA Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Current Rating 820mA Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Current - Saturation 900mA Shielding Unshielded DC Resistance (DCR) 360 mOhm Max Q @ Freq 12 @ 2.52MHz	
Shielding DC Resistance (DCR) Q @ Freq Unshielded 360 mOhm Max 12 @ 2.52MHz	
DC Resistance (DCR) Q @ Freq 12 @ 2.52MHz	
Q @ Freq 12 @ 2.52MHz	
-	
Frequency - Self Resonant 12.2MHz	
= -	
Ratings -	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Frequency - Test 100kHz	
Features -	
Mounting Type Surface Mount	
Package / Case Nonstandard	
Supplier Device Package -	
Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm	m)

Height - Seated (Max) 0.130" (3.30mm) Report errors?

SDR1030-680M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDR1030-680M Payment Methods



















SDR1030-680M Shipping Methods













If you have any question about SDR1030-680M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com