



### **SDS60UT09 Information**



For Reference Only

Part Number SDS60UT09
Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 5V 24V -12V 60W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **SDS60UT09 Specifications**

Manufacturer Part Number         SDS60UT09           Manufacturer         XP Power           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         SDS           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         24V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6A, 2A, 800mA           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         SDS           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         24V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6A, 2A, 800mA           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Manufacturer Part Number	SDS60UT09
Package         -           Series         SDS           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         24V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6A, 2A, 800mA           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Manufacturer	XP Power
Package         -           Series         SDS           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         24V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6A, 2A, 800mA           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         SDS           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         24V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6A, 2A, 800mA           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)		AC DC Converters
Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         24V           Voltage - Output 3         -12V           Voltage - Output 4         -           Current - Output (Max)         6A, 2A, 800mA           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Package	-
Number of Outputs3Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 1 $5\text{V}$ Voltage - Output 2 $24\text{V}$ Voltage - Output 3 $-12\text{V}$ Voltage - Output 4-Current - Output (Max) $6A, 2A, 800\text{mA}$ Power (Watts) $60\text{W}$ ApplicationsITE (Commercial)Voltage - Isolation $3\text{kV} (3000\text{V})$ Efficiency $80\%$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.20^{\circ}\text{H} (127.0\text{mm x } 76.2\text{mm x } 30.5\text{mm})$	Series	SDS
Voltage - Input90 ~ 264 VACVoltage - Output 15VVoltage - Output 224VVoltage - Output 3-12VVoltage - Output 4-Current - Output (Max)6A, 2A, 800mAPower (Watts)60WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency80%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Туре	Open Frame
Voltage - Output 1  Voltage - Output 2  24V  Voltage - Output 3  -12V  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Size / Dimension  5 V  24V  24V  24V  24V  - 26V  24V  - 26V  - 26V  - 26V  40V  - 26V  - 26V  40V  40V  40V  40V  40V  40V  40V  4	Number of Outputs	3
Voltage - Output 2  Voltage - Output 3  -12V  Voltage - Output 4  -Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Size / Dimension  24V  24V  24V  24V  -12V  -	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Size / Dimension  -12V  -	Voltage - Output 1	5V
Voltage - Output 4  Current - Output (Max)  6A, 2A, 800mA  Power (Watts)  60W  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  80%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Voltage - Output 2	24V
Current - Output (Max) 6A, 2A, 800mA  Power (Watts) 60W  Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 80%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Voltage - Output 3	-12V
Power (Watts) 60W  Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 80%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 80%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Current - Output (Max)	6A, 2A, 800mA
Voltage - Isolation 3kV (3000V)  Efficiency 80%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Power (Watts)	60W
Efficiency 80%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Applications	ITE (Commercial)
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Efficiency	80%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.5mm)
		Report errors?

#### **SDS60UT09 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **SDS60UT09 Payment Methods**





















### **SDS60UT09 Shipping Methods**













If you have any question about SDS60UT09, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com