



SDT-S-109LMR2,000 Information

Part Number SDT-S-109LMR2,000

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 5A 9V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDT-S-109LMR2,000 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Power Relays, Over 2 Amps Package - Series SDT-R, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage Turn On Voltage (Max) 6.75 VDC
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSDT-R, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7 mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)6.75 VDC
Package - Series SDT-R, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage (Max) 6.75 VDC
Package - Series SDT-R, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Series SDT-R, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Coil Type Non Latching Coil Current 16.7mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Coil Current 16.7mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC
Turn On Voltage (Max) 6.75 VDC
Turn Off Voltage (Min) 0.9 VDC
Operate Time 15ms
Release Time 5ms
Features Insulation - Class E
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

SDT-S-109LMR2,000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDT-S-109LMR2,000 Payment Methods



















SDT-S-109LMR2,000 Shipping Methods













If you have any question about SDT-S-109LMR2,000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com