



SDX15A2 Information



For Reference Only

Part Number SDX15A2

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR TEMP COMP 15PSIA DIP

Package 6-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDX15A2 Specifications

Manufacturer Part NumberSDX15A2ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage6-DIP ModuleSeriesSDXPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 90 mV (12V)Accuracy±1%Voltage - Supply20VPort SizeMale - 0.11" (2.67mm) TubePort StyleBarblessFeaturesTemperature Compensated
Category Sensors, Transducers Pressure Sensors, Transducers Package 6-DIP Module Series SDX Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±1% Voltage - Supply Port Size Male - 0.11" (2.67mm) Tube Port Style
Pressure Sensors, Transducers Package 6-DIP Module Series SDX Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±1% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless
Package 6-DIP Module Series SDX Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±1% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless
Series SDX Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±1% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless
Pressure Type Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±1% Voltage - Supply Port Size Male - 0.11" (2.67mm) Tube Port Style Absolute 15 PSI (103.42 kPa) Wheatstone Bridge 0 mV ~ 90 mV (12V) 4 curacy 5 mV (12V) 4 curacy 5 mV (12V) 5 mV (12V) 6 mV ~ 90 mV (12V) 7 mV ~ 90 mV (12V) 7 mV ~ 90 mV (12V) 7 mV ~ 90 mV ~ 90 mV (12V) 7 mV ~ 90 mV ~ 90 mV (12V) 7 mV ~ 90 mV ~ 90 mV (12V) 7 mV ~ 90 mV ~
Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±1% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 90 \text{ mV} (12\text{V})$ Accuracy $\pm 1\%$ Voltage - Supply 20V Port SizeMale - 0.11 " (2.67mm) TubePort StyleBarbless
Output $0 \text{ mV} \sim 90 \text{ mV} (12\text{V})$ Accuracy $\pm 1\%$ Voltage - Supply 20V Port Size $\text{Male - 0.11" (2.67\text{mm}) Tube}$ Port Style Barbless
Accuracy $\pm 1\%$ Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless
Voltage - Supply Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless
Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless
Port Style Barbless
Features Temperature Compensated
Termination Style PCB
Maximum Pressure 30 PSI (206.84 kPa)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case 6-DIP Module
Supplier Device Package -
Report errors?

SDX15A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDX15A2 Payment Methods



















SDX15A2 Shipping Methods













If you have any question about SDX15A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com