

SDX15G2-A Information



For Reference Only

Part Number SDX15G2-A

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS GAUGE 15PSI

Package 6-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDX15G2-A Specifications

Manufacturer SDX15G2-A Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 6-DIP Module Series SDX Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±0.25% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package -		
Category Sensors, Transducers Pressure Sensors, Transducers Package 6-DIP Module Series SDX Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output (12V) Accuracy ±0.25% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case G-DIP Module Supplier Device Package	Manufacturer Part Number	SDX15G2-A
Package 6-DIP Module Series SDX Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±0.25% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package6-DIP ModuleSeriesSDXPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 90 mV (12V)Accuracy±0.25%Voltage - Supply20VPort SizeMale - 0.11" (2.67mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case6-DIP ModuleSupplier Device Package-	Category	Sensors, Transducers
Series SDX Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±0.25% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 90 mV (12V) Accuracy ±0.25% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package	Package	6-DIP Module
Operating Pressure Output Type Wheatstone Bridge Output Output On W ~ 90 mV (12V) Accuracy ±0.25% Voltage - Supply Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package - 15 PSI (103.42 kPa) Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge 10 mV ~ 90 mV (12V) ### 12 mV — 40.25% #### 200 mV — 40.25% ### 200 mV — 40.25% #### 200 mV — 40.25% ### 200 mV — 40.25% #### 200 mV — 40.25% #### 200 mV — 40.25% ####	Series	SDX
Output Type Output Outp	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 90 \text{ mV} (12\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply 20V Port SizeMale - 0.11 " (2.67mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure $30 \text{ PSI} (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 6-DIP Module Supplier Device Package $-$	Operating Pressure	15 PSI (103.42 kPa)
Accuracy ±0.25% Voltage - Supply 20V Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package	Output	0 mV ~ 90 mV (12V)
Port Size Male - 0.11" (2.67mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package -	Accuracy	±0.25%
Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package	Voltage - Supply	20V
Features Temperature Compensated Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package -	Port Size	Male - 0.11" (2.67mm) Tube
Termination Style PCB Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package -	Port Style	Barbless
Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package -	Features	Temperature Compensated
Operating Temperature -40°C ~ 85°C Package / Case 6-DIP Module Supplier Device Package -	Termination Style	PCB
Package / Case 6-DIP Module Supplier Device Package -	Maximum Pressure	30 PSI (206.84 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	6-DIP Module
Report errors?	Supplier Device Package	-
		Report errors?

SDX15G2-A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDX15G2-A Payment Methods





















SDX15G2-A Shipping Methods













If you have any question about SDX15G2-A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com