

SEE75N2-16.0 Information

Heisener.com

Part Number SEE75N2-16.0

Manufacturer Sanken

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

AC/DC DESKTOP ADAPTER 16V 75W **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SEE75N2-16.0 Specifications

Manufacturer Part Number SEE75N2-16.0 Manufacturer Sanken Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SEE75 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 16V Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SEE75 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 16V Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Manufacturer Part Number	SEE75N2-16.0
Package - Series SEE75 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 16V Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Manufacturer	Sanken
Package - Series SEE75 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 16V Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series SEE75 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 16V Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output16VCurrent - Output (Max)4.69APower (Watts)75WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)Efficiency88%Operating Temperature-Output Connector-Size / Dimension3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 16V Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Series	SEE75
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 16V Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 16V Current - Output (Max) 4.69A Power (Watts) No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature Output Connector Size / Dimension 90 ~ 264 VAC 16V 16V 16V 16V 16V 17E (Commercial) 17E 17E 17E 18E 17E 18E 18E 18E	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature Output Connector Size / Dimension 16V 4.69A 75W 75W 75W 75W 75W 80mW (Max) 90mW (Max) 17E (Commercial) 17E (Commercial)	Input Type	Cord (Sold Separately)
Current - Output (Max) 4.69A Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 75W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Voltage - Output	16V
No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Current - Output (Max)	4.69A
Polarization - Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Power (Watts)	75W
Applications ITE (Commercial) Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	No Load Power Consumption	300mW (Max)
Efficiency 88% Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Polarization	-
Operating Temperature - Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Applications	ITE (Commercial)
Output Connector - Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Efficiency	88%
Size / Dimension 3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)	Operating Temperature	-
	Output Connector	-
Report errors?	Size / Dimension	3.46" L x 1.54" W x 1.06" H (88.0mm x 39.0mm x 27.0mm)
		Report errors?

SEE75N2-16.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SEE75N2-16.0 Payment Methods



















SEE75N2-16.0 Shipping Methods













If you have any question about SEE75N2-16.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com