


SF-1206F050-2

Request a Quote

SF-1206F050-2 Information

	Part Number	SF-1206F050-2
www.heisener.com	Manufacturer	Bourns Inc.
	Category	Circuit Protection Fuses
F	Description	FUSE BOARD MNT 500MA 63VDC 1206
	Package	1206 (3216 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SF-1206F050-2 Specifications

Manufacturer Bourns Inc. Category Circuit Protection Fuses Fuses Package 1206 (3216 Metric) Streiss SingIFuse? SF-1206F Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 500mA Voltage Rating - AC - Voltage Rating - DC 63V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.011 Approvals UL Operating Temperature -40°C ~ 105°C Color -			
CategoryCircuit ProtectionFusesPackage1206 (3216 Metric)SeriesSinglFuse? SF-1206FFuse TypeBoard Mount (Catridge Style Excluded)Current Rating500mAVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.011ApprovalsULOperating Temperature40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Manufacturer Part Number	SF-1206F050-2	
FusesPackage1206 (3216 Metric)SeriesSinglFuse? SF-1206FFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating500mAVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting 12t0.011ApprovalsULOperating Temperature-40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Manufacturer	Bourns Inc.	
Package1206 (3216 Metric)SeriesSinglFuse? SF-1206FFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating500mAVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMetring 12t0.011ApprovalsIUOperating Temperature-40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Category	Circuit Protection	
Series SinglFuse? SF-1206F Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 500mA Voltage Rating - AC - Voltage Rating - DC 63V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.011 Approvals UL Operating Temperature -40°C ~ 105°C Color - Size / Dimension 0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating500mAVoltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.011ApprovalsULOperating Temperature-40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Package	1206 (3216 Metric)	
Current Rating 500mA Voltage Rating - AC - Voltage Rating - DC 63V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.011 Approvals UL Operating Temperature -40°C ~ 105°C Color - Size / Dimension 0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Series	SinglFuse? SF-1206F	
Voltage Rating - AC-Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.011ApprovalsULOperating Temperature-40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.011ApprovalsULOperating Temperature-40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Current Rating	500mA	
Response TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.011ApprovalsULOperating Temperature-40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Voltage Rating - AC	-	
Package / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.011ApprovalsULOperating Temperature-40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Voltage Rating - DC	63V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.011ApprovalsULOperating Temperature-40°C ~ 105°CColor-Size / Dimension0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Response Time	Fast	
Breaking Capacity @ Rated Voltage 50A Melting I2t 0.011 Approvals UL Operating Temperature -40°C ~ 105°C Color - Size / Dimension 0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Package / Case	1206 (3216 Metric)	
Melting I2t 0.011 Approvals UL Operating Temperature -40°C ~ 105°C Color - Size / Dimension 0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Mounting Type	Surface Mount	
Approvals UL Operating Temperature -40°C ~ 105°C Color - Size / Dimension 0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Breaking Capacity @ Rated Voltage	50A	
Operating Temperature -40°C ~ 105°C Color - Size / Dimension 0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Melting I2t	0.011	
Color - Size / Dimension 0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Approvals	UL	
Size / Dimension 0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	Operating Temperature	-40°C ~ 105°C	
	Color	-	
Report errors?	Size / Dimension	0.122" L x 0.061" W x 0.024" H (3.10mm x 1.55mm x 0.60mm)	
		Repor	rt errors?

E-mail: salesdept@heisener.com

SF-1206F050-2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SF-1206F050-2 Payment Methods WIRE transfer PayPal Methods SF-1206F050-2 Shipping Methods FedEx. O OOO THE SECOND

If you have any question about SF-1206F050-2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com