

SF7282-2SG-3ES Information



For Reference Only

Part NumberSF7282-2SG-3ESManufacturerConxall/SwitchcraftCategoryConnectors, Interconnects
Circular Connectors

Description CONN RCPT 2POS PNL MNT SKT

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SF7282-2SG-3ES Specifications

| Manufacturer Part Number SF7282-28G-3ES Manufacturer Conxall/Switchcraft Category Connectors, Interconnects Package - Series Shielded Mini-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - Report errors? | | |
|---|--------------------------|---|
| Category Circular Connectors Package Package Series Shielded Mini-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Courrent Rating - Connectors, Interconnects Circular Connectors Shielded Connectors Circular Connectors Shielded Contact Finish Copper Alloy, Nickel Plated Courrent Rating - Connectors Circular Connectors Shielded Contact Finish Copper Alloy, Nickel Plated Contact Finish Copper Alloy Courrent Rating | Manufacturer Part Number | SF7282-2SG-3ES |
| Circular Connectors Package - Series Shielded Mini-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating - Circular Connectors Shielded Mini-Con-X? Receptacle, Female Sockets Anielded Alini-Con-X? Receptacle, Female Sockets Shielded Features Shielded Contact Finish Gold Current Rating - Circular Connectors Shielded Contact Finish Gold Current Rating - Circular Connectors Shielded - Contact Finish Copper Alloy, Nickel Plated Contact Finish Gold Current Rating | Manufacturer | Conxall/Switchcraft |
| Package - Shielded Mini-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating | Category | Connectors, Interconnects |
| Series Shielded Mini-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | | Circular Connectors |
| Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Package | - |
| Number of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating- | Series | Shielded Mini-Con-X? |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating | Number of Positions | 2 |
| Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Shell Size - Insert | - |
| Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Shell Size, MIL | - |
| Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Mounting Type | Panel Mount, Bulkhead - Front Side Nut |
| Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Termination | Solder Cup |
| Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating - | Fastening Type | Threaded |
| Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Orientation | Keyed |
| Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Ingress Protection | IP66/68 - Dust Tight, Water Resistant, Waterproof |
| Features Shielded Voltage - Rated 600VAC/DC Current Rating - | Shell Material, Finish | Copper Alloy, Nickel Plated |
| Voltage - Rated 600VAC/DC Current Rating - | Contact Finish | Gold |
| Current Rating - | Features | Shielded |
| | Voltage - Rated | 600VAC/DC |
| Report errors? | Current Rating | - |
| | | Report errors? |

SF7282-2SG-3ES Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SF7282-2SG-3ES Payment Methods





















SF7282-2SG-3ES Shipping Methods













If you have any question about SF7282-2SG-3ES, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com