

SF7282-3PG-3ES Information



For Reference Only

Part Number SF7282-3PG-3ES

Manufacturer Conxall/Switchcraft

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 3POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SF7282-3PG-3ES Specifications

Manufacturer Part Number SF7282-3PG-3ES Manufacturer Conxall/Switchcraft Category Connectors, Interconnects Package - Series Shielded Mini-Con-X? Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - Report errors?			
CategoryConnectors, InterconnectsPackage-SeriesShielded Mini-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Manufacturer Part Number	SF7282-3PG-3ES	
Package - Shielded Mini-Con-X? Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features Shielded Voltage - Rated Overtet Rating - Shielded Current Rating - Shielded Current Rating - Shielded Current Rating - Shielded Contact Finish GOOVAC/DC Current Rating	Manufacturer	Conxall/Switchcraft	
Package-SeriesShielded Mini-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Category	Connectors, Interconnects	
Series Shielded Mini-Con-X? Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -		Circular Connectors	
Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Package	-	
Number of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Series	Shielded Mini-Con-X?	
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Coverage Attention Current Rating	Connector Type	Receptacle, Male Pins	
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating	Number of Positions	3	
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Shell Size - Insert	-	
Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Shell Size, MIL	-	
Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut	
Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Termination	Solder Cup	
Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating -	Fastening Type	Threaded	
Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Orientation	Keyed	
Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof	
Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Shell Material, Finish	Copper Alloy, Nickel Plated	
Voltage - Rated 600VAC/DC Current Rating -	Contact Finish	Gold	
Current Rating -	Features	Shielded	
-	Voltage - Rated	600VAC/DC	
Report errors?	Current Rating	-	
		Report errors	?

SF7282-3PG-3ES Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SF7282-3PG-3ES Payment Methods





















SF7282-3PG-3ES Shipping Methods













If you have any question about SF7282-3PG-3ES, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com