

SF7381-5SG-3ES Information

Manufact Category Heisener.com

Part Number SF7381-5SG-3ES

Manufacturer Conxall/Switchcraft

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 5POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SF7381-5SG-3ES Specifications

Manufacturer Part Number SF7381-SSG-3ES Manufacturer Conxall/Switchcraft Category Connectors, Interconnects Package - Series Shielded Mini-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesShielded Mini-Con-X?Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Manufacturer Part Number	SF7381-5SG-3ES
Package - Shielded Mini-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features Shielded Voltage - Rated Overnet Rating - Shielded Current Rating - Shielded Current Rating - Shielded Current Rating - Shielded Contact Finish GOOVAC/DC Current Rating	Manufacturer	Conxall/Switchcraft
Package-SeriesShielded Mini-Con-X?Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Category	Connectors, Interconnects
Series Shielded Mini-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Package	-
Number of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Series	Shielded Mini-Con-X?
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Courrent Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating	Number of Positions	5
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC/DCCurrent Rating-	Shell Size - Insert	-
Termination Solder Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation Keyed Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Termination	Solder
Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating -	Fastening Type	Threaded
Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Orientation	Keyed
Contact Finish Gold Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated 600VAC/DC Current Rating -	Shell Material, Finish	Copper Alloy, Nickel Plated
Voltage - Rated 600VAC/DC Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shielded
-	Voltage - Rated	600VAC/DC
Report errors?	Current Rating	-
		Report errors?

SF7381-5SG-3ES Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SF7381-5SG-3ES Payment Methods



















SF7381-5SG-3ES Shipping Methods













If you have any question about SF7381-5SG-3ES, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com