

**SFH11-PBPC-D17-RA-BK Information**


For Reference Only

**Part Number** [SFH11-PBPC-D17-RA-BK](#)  
**Manufacturer** Sullins Connector Solutions  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Receptacles, Female Sockets](#)  
**Description** CONN HEADR FEMALE 34PS .1" R/A AU  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**SFH11-PBPC-D17-RA-BK Specifications**

|                                   |  |
|-----------------------------------|--|
| Manufacturer Part Number          | <a href="#">SFH11-PBPC-D17-RA-BK</a>   |
| Manufacturer                      | Sullins Connector Solutions  |
| Category                          | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Receptacles, Female Sockets</a> |
| Package                           | -  |
| Series                            | SFH11  |
| Connector Type                    | Header   |
| Contact Type                      | Female Socket  |
| Style                             | Board to Board   |
| Number of Positions               | 34   |
| Number of Positions Loaded        | All  |
| Pitch - Mating                    | 0.100" (2.54mm)  |
| Number of Rows                    | 2  |
| Row Spacing - Mating              | 0.100" (2.54mm)  |
| Mounting Type                     | Through Hole, Right Angle  |
| Termination                       | Solder   |
| Fastening Type                    | Push-Pull  |
| Contact Finish - Mating           | Gold   |
| Contact Finish Thickness - Mating | Flash  |
| Insulation Color                  | Black  |
| Insulation Height                 | 0.236" (6.00mm)  |
| Contact Length - Post             | 0.106" (2.69mm)  |
| Operating Temperature             | -40°C ~ 105°C  |
| Material Flammability Rating      | UL94 V-0   |

|                        |                |
|------------------------|----------------|
| Contact Finish - Post  | Gold           |
| Mated Stacking Heights | -              |
| Ingress Protection     | -              |
| Features               | Polarizing Key |

[Report errors?](#)

### SFH11-PBPC-D17-RA-BK Guarantees



**Quality Guarantees**

We provide 90 days warranty. \*  
 If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



**Service Guarantees**

We guarantee 100% customer satisfaction.  
 Our experienced sales team and tech support team back our services to satisfy all our customers.

### SFH11-PBPC-D17-RA-BK Payment Methods



### SFH11-PBPC-D17-RA-BK Shipping Methods



If you have any question about SFH11-PBPC-D17-RA-BK, please do not hesitate to contact us!  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)