

SFH620A-3X006 Information

Heisener.com

Part Number SFH620A-3X006

Manufacturer Vishay Semiconductor Opto Division

Category

Optoisolators - Transistor, Photovoltaic Output

Description OPTOISOLATOR 5.3KV TRANS 4DIP

4-DIP (0.400", 10.16mm) **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SFH620A-3X006 Specifications

Manufacturer Part Number SFH620A-3X006 Manufacturer Vishay Semiconductor Opto Division Category Isolators Optoisolators - Transistor, Photovoltaic Output Package 4-DIP (0.400", 10.16mm) Series - Number of Channels 1 Current Transfer Ratio (Min) 100% @ 10mA Current Transfer Ratio (Max) 320% @ 10mA Turn On / Turn Off Time (Typ) 3µs, 2.3µs Rise / Fall Time (Typ) 2µs, 2µs Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vec Saturation (Max) 400mV Operating Temperature -55°C - 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	•	
Category Isolators Optoisolators - Transistor, Photovoltaic Output Package 4-DIP (0.400", 10.16mm) Series - Number of Channels 1 Voltage - Isolation 5300Vrms Current Transfer Ratio (Min) 100% @ 10mA Current Transfer Ratio (Max) 320% @ 10mA Turn On / Turn Off Time (Typ) 3μs, 2.3μs Rise / Fall Time (Typ) 2μs, 2μs Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vcc Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Manufacturer Part Number	SFH620A-3X006
Package 4-DIP (0.400", 10.16mm) Series - Number of Channels 1 Voltage - Isolation 5300Vrms Current Transfer Ratio (Min) 100% @ 10mA Current Transfer Ratio (Max) 320% @ 10mA Turn On / Turn Off Time (Typ) 3μs, 2.3μs Rise / Fall Time (Typ) 2μs, 2μs Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vec Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Manufacturer	Vishay Semiconductor Opto Division
Package 4-DIP (0.400", 10.16mm) Series - Number of Channels 1 Voltage - Isolation 5300Vrms Current Transfer Ratio (Min) 100% @ 10mA Current Transfer Ratio (Max) 320% @ 10mA Turn On / Turn Off Time (Typ) 3μs, 2.3μs Rise / Fall Time (Typ) 2μs, 2μs Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Category	Isolators
Series - Number of Channels 1 Voltage - Isolation 5300Vrms Current Transfer Ratio (Min) 100% @ 10mA Current Transfer Ratio (Max) 320% @ 10mA Turn On / Turn Off Time (Typ) 3μs, 2.3μs Rise / Fall Time (Typ) 2μs, 2μs Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP		Optoisolators - Transistor, Photovoltaic Output
Number of Channels 1 Voltage - Isolation 5300Vrms Current Transfer Ratio (Min) 100% @ 10mA Current Transfer Ratio (Max) 320% @ 10mA Turn On / Turn Off Time (Typ) 3μs, 2.3μs Rise / Fall Time (Typ) 2μs, 2μs Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Package	4-DIP (0.400", 10.16mm)
Voltage - Isolation5300VrmsCurrent Transfer Ratio (Min)100% @ 10mACurrent Transfer Ratio (Max)320% @ 10mATurn On / Turn Off Time (Typ)3μs, 2.3μsRise / Fall Time (Typ)2μs, 2μsInput TypeAC, DCOutput TypeTransistorVoltage - Output (Max)70VCurrent - Output / Channel50mAVoltage - Forward (Vf) (Typ)1.25VCurrent - DC Forward (If) (Max)60mAVce Saturation (Max)400mVOperating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / Case4-DIP (0.400", 10.16mm)Supplier Device Package4-DIP	Series	-
Current Transfer Ratio (Min) 100% @ 10mA Current Transfer Ratio (Max) 320% @ 10mA Turn On / Turn Off Time (Typ) 3μs, 2.3μs Rise / Fall Time (Typ) 2μs, 2μs Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Number of Channels	1
Current Transfer Ratio (Max)320% @ 10mATurn On / Turn Off Time (Typ)3μs, 2.3μsRise / Fall Time (Typ)2μs, 2μsInput TypeAC, DCOutput TypeTransistorVoltage - Output (Max)70VCurrent - Output / Channel50mAVoltage - Forward (Vf) (Typ)1.25VCurrent - DC Forward (If) (Max)60mAVce Saturation (Max)400mVOperating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / Case4-DIP (0.400", 10.16mm)Supplier Device Package4-DIP	Voltage - Isolation	5300Vrms
Turn On / Turn Off Time (Typ) $3\mu s, 2.3\mu s$ Rise / Fall Time (Typ) $2\mu s, 2\mu s$ Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package	Current Transfer Ratio (Min)	100% @ 10mA
Rise / Fall Time (Typ)2μs, 2μsInput TypeAC, DCOutput TypeTransistorVoltage - Output (Max)70VCurrent - Output / Channel50mAVoltage - Forward (Vf) (Typ)1.25VCurrent - DC Forward (If) (Max)60mAVce Saturation (Max)400mVOperating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / Case4-DIP (0.400", 10.16mm)Supplier Device Package4-DIP	Current Transfer Ratio (Max)	320% @ 10mA
Input Type AC, DC Output Type Transistor Voltage - Output (Max) 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Turn On / Turn Off Time (Typ)	3μs, 2.3μs
Output Type Transistor 70V Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package	Rise / Fall Time (Typ)	2μs, 2μs
Voltage - Output (Max) Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Input Type	AC, DC
Current - Output / Channel 50mA Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Output Type	Transistor
Voltage - Forward (Vf) (Typ) 1.25V Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Voltage - Output (Max)	70V
Current - DC Forward (If) (Max) 60mA Vce Saturation (Max) 400mV Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Current - Output / Channel	50mA
Vce Saturation (Max)400mVOperating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / Case4-DIP (0.400", 10.16mm)Supplier Device Package4-DIP	Voltage - Forward (Vf) (Typ)	1.25V
Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Current - DC Forward (If) (Max)	60mA
Mounting Type Through Hole Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Vce Saturation (Max)	400mV
Package / Case 4-DIP (0.400", 10.16mm) Supplier Device Package 4-DIP	Operating Temperature	-55°C ~ 100°C
Supplier Device Package 4-DIP	Mounting Type	Through Hole
	Package / Case	4-DIP (0.400", 10.16mm)
Report errors?	Supplier Device Package	4-DIP
		Report errors?

SFH620A-3X006 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SFH620A-3X006 Payment Methods





















SFH620A-3X006 Shipping Methods













If you have any question about SFH620A-3X006, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com