

## SFM315-LPGE-D23-SP-BK Information

For the pricing/inventory/lead time, please contact us	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## SFM315-LPGE-D23-SP-BK Specifications

ManufacturerSulfins Connector SolutionsCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSFM315Connector TypeHeaderContact TypeFemale SocketSylveBoard to BoardNumber of Positions46Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.039" (1.00mm)Number of Rows0.039" (1.00mm)Number of RowsSolderFerminationSolderFortinationGoldContact Finish - MatingGoldContact Finish - MatingIopin (0.25µm)Insulation ColorBackInsulation Finish - MatingIopin (0.30mm)Contact Finish - MatingIopin (0.30mm)Insulation Finish - MatingIopin (0.30mm)Contact Finish - MatingIopin (0.30mm)Insulation FieldsJourne (Journe)Finish - MatingIopin (0.25µm)Insulation FieldsIopin (0.30mm)Insulation FieldsIopin (0.25µm)Insulation FieldsIopin (0.30mm)Insulation FieldsIop	Manufacturer Part Number	SFM315-LPGE-D23-SP-BK
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSFM315Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.039" (1.00mm)Number of Rows0.039" (1.00mm)Number of Rows0.039" (1.00mm)FerminationSolderFortin StringOlderFortin StringSolderFortin StringSolderFortin StringSolderFortin StringSolderFastening TypeInjun (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.00mm)Fortact Length - Post-		
Icctangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSFM315Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions LoadedAllPitch - Mating0.039° (1.00mm)Number of Rows2Row Spacing - Mating0.039° (1.00mm)Mounting Type0.039° (1.00mm)FerninationSolderForting TypeOlderContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingBlackInsulation ColorBlackInsulation FinishSilosSilosSilosContact Finish - MatingSilosInsulation FinishSilos <tr <td=""><tr <td="">Silos</tr></tr>	Manufacturer	Sullins Connector Solutions
Package-SeriesSFM315Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSolderFarminationSolderFastening TypeOldContact Finish - MatingOldContact Finish - MatingIpin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Category	Connectors, Interconnects
SeriesSFM315Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFastening TypeSurface MountContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingIupin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.00mm)Contact Length - Post-	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions46Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Series	SFM315
StyleBoard to BoardNumber of Positions46Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting Type0.039" (1.00mm)TerminationSurface MountFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Connector Type	Header
Number of Positions46Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Style	Board to Board
Pitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting Type0.039" (1.00mm)TerminationSurface MountFastening TypeSolderFontact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Number of Positions	46
Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Number of Positions Loaded	All
Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Pitch - Mating	0.039" (1.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Row Spacing - Mating	0.039" (1.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Termination	Solder
Contact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post-	Contact Finish - Mating	Gold
Insulation Height0.130" (3.30mm)Contact Length - Post-	Contact Finish Thickness - Mating	10μin (0.25μm)
Contact Length - Post -	Insulation Color	Black
-	Insulation Height	0.130" (3.30mm)
Operating Temperature $-40^{\circ}$ C $\sim 125^{\circ}$ C	Contact Length - Post	-
	Operating Temperature	-40°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	Board Guide	
		D ( )

Report errors?

## SFM315-LPGE-D23-SP-BK Guarantees **Quality Guarantees** We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition. **Service Guarantees** SFRVI We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers. SFM315-LPGE-D23-SP-BK Payment Methods WIRE transfer **PayPal** S MoneyGram Alipay VISA DISCOVER SFM315-LPGE-D23-SP-BK Shipping Methods **ZHL\_ FedEx. 10 TNT**

If you have any question about SFM315-LPGE-D23-SP-BK, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com