

SFP37S20K238B

SFP37S20K238B Information





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SFP37S20K238B Specifications

ManufacturerCornell Dubilier Electronics (CDE)CapacitorsCapacitorsPackageRadial, CanSeriesSFCapacitance20µFTolerance±10%Voltage Rating - DC370VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870° Dia (47.50mm), LipHeight - Seated (Max)2.500° (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810° (20.57mm)ApplicationsMotor RunFeatures-		
CategoryCapacitorsFilm CapacitorsPackageRadial, CanSeriesSFCapacitance20µFColerance±10%Voltage Rating - AC370VVoltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedDoperating Temperature-40°C ~ 70°CMounting TypeRadial, CanSize / Dimension1.870° Dia (47.50mm), LipBeight - Seated (Max)2.500° (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810° (20.57mm)Features-Features-Features-Features-Features-Start Start-Start Start Start-Start Start Start-Start Start Start-Start Start Start Start-Start Start S	Manufacturer Part Number	SFP37S20K238B
Filn CapacitorsPackageRadial, CanSeriesSFCapacitance20µFTolerance±10%Voltage Rating - AC370VVoltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870° Dia (47.50mm), LipHeight - Seated (Max)2.500° (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810° (20.57mm)Features-	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, CanSeriesSFCapacitance20µFTolerance±10%Voltage Rating - AC370VVoltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870° Dia (47.50mm), LipHeight - Seated (Max)2.500° (63.50mm)Lead Spacing0.810° (20.57mm)ApplicationsMotor RunFeatures-	Category	Capacitors
SeriesSFCapacitance20μFTolerance±10%Voltage Rating - AC370VVoltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870° Dia (47.50mm), LipHeight - Seated (Max)2.500° (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810° (20.57mm)Features-		Film Capacitors
Capacitance20µFTolerance±10%Voltage Rating - AC370VVoltage Rating - DC-Dielectric MaterialPolyproylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)Lead Spacing0.810" (20.57mm)ApplicationsMotor RunFeatures-	Package	Radial, Can
Tolerance±10%Voltage Rating - AC370VVoltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)ApplicationsMotor Run	Series	SF
Voltage Rating - AC370VVoltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)Applications-Features-	Capacitance	20µF
Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870° Dia (47.50mm), LipHeight - Seated (Max)2.500° (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810° (20.57mm)Applications-Features-	Tolerance	$\pm 10\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)Applications-Features-	Voltage Rating - AC	370V
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)ApplicationsMotor RunFeatures-	Voltage Rating - DC	-
Operating Temperature-40°C ~ 70°CMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)Applications-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeChassis MountMounting TypeChassis MountPackage / CaseRadial, CanSize / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)ApplicationsMotor RunFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadial, CanSize / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)ApplicationsMotor RunFeatures-	Operating Temperature	-40°C ~ 70°C
Size / Dimension1.870" Dia (47.50mm), LipHeight - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)ApplicationsMotor RunFeatures-	Mounting Type	Chassis Mount
Height - Seated (Max)2.500" (63.50mm)TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)ApplicationsMotor RunFeatures-	Package / Case	Radial, Can
TerminationQuick Connect, DisconnectLead Spacing0.810" (20.57mm)ApplicationsMotor RunFeatures-	Size / Dimension	1.870" Dia (47.50mm), Lip
Lead Spacing0.810" (20.57mm)ApplicationsMotor RunFeatures-	Height - Seated (Max)	2.500" (63.50mm)
Applications Motor Run Features -	Termination	Quick Connect, Disconnect
Features -	Lead Spacing	0.810" (20.57mm)
	Applications	Motor Run
Report errors?	Features	-
		Report errors?

SFP37S20K238B Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SFP37S20K238B Payment Methods





If you have any question about SFP37S20K238B, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com