



SFY3-DC21V Information

heisene

For Reference Only

Part Number SFY3-DC21V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY SAFETY 4PST 6A 21V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SFY3-DC21V Specifications

Manufacturer Part Number SFY3-DC21V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series SF-Y Relay Type Safety Coil Type Non Latching Coil Current 32mA Coil Voltage 21VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC
Category Relays Power Relays, Over 2 Amps Package - Series SF-Y Relay Type Safety Coil Type Non Latching Coil Current 32mA Coil Voltage 21VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max
Package - Series SF-Y Relay Type Safety Coil Type Non Latching Coil Current 32mA Coil Voltage 21VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max
Package - Series SF-Y Relay Type Safety Coil Type Non Latching Coil Current 32mA Coil Voltage 21VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max
SeriesSF-YRelay TypeSafetyCoil TypeNon LatchingCoil Current32mACoil Voltage21VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 30VDC - Max
Relay Type Coil Type Non Latching Coil Current 32mA Coil Voltage 21VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max
Coil TypeNon LatchingCoil Current32mACoil Voltage21VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 30VDC - Max
Coil Current 32mA Coil Voltage 21VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max
Coil Voltage 21VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max
Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max
Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max
Switching Voltage 250VAC, 30VDC - Max
Turn On Voltage (May)
Turn On voltage (wax)
Turn Off Voltage (Min) 3.2 VDC
Operate Time 20ms
Release Time 10ms
Features -
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

SFY3-DC21V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SFY3-DC21V Payment Methods



















SFY3-DC21V Shipping Methods













If you have any question about SFY3-DC21V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com