



SFY4-DC21V Information



For Reference Only

Part Number SFY4-DC21V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY SAFETY 6PST 6A 21V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SFY4-DC21V Specifications

Manufacturer Part Number SFY4-DC21V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series SF-Y Relay Type Safety Coil Type Non Latching Coil Current 32mA Coil Voltage 21VDC Contact Form 6PST (4 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesSF-YRelay TypeSafetyCoil TypeNon LatchingCoil Current32mACoil Voltage21 VDCContact Form6PST (4 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)15.8 VDCTurn Off Voltage (Min)3.2 VDCOperate Time20msRelease Time10msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	SFY4-DC21V
Package - Series SF-Y Relay Type Safety Coil Type Non Latching Coil Current 32mA Coil Voltage 21VDC Contact Form 6PST (4 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Manufacturer	Panasonic Electric Works
Package-SeriesSF-YRelay TypeSafetyCoil TypeNon LatchingCoil Current32mACoil Voltage21VDCContact Form6PST (4 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)15.8 VDCTurn Off Voltage (Min)3.2 VDCOperate Time20msRelease Time10msFeatures-Mounting TypeThrough Hole	Category	Relays
SeriesSF-YRelay TypeSafetyCoil TypeNon LatchingCoil Current32mACoil Voltage21VDCContact Form6PST (4 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)15.8 VDCTurn Off Voltage (Min)3.2 VDCOperate Time20msRelease Time10msFeatures-Mounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type Safety Coil Type Non Latching Coil Current 32mA Coil Voltage 21VDC Contact Form 6PST (4 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Package	-
Coil TypeNon LatchingCoil Current32mACoil Voltage21VDCContact Form6PST (4 Form A, 2 Form B)Contact Rating (Current)6ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)15.8 VDCTurn Off Voltage (Min)3.2 VDCOperate Time20msRelease Time10msFeatures-Mounting TypeThrough Hole	Series	SF-Y
Coil Current 32mA Coil Voltage 21VDC Contact Form 6PST (4 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Relay Type	Safety
Coil Voltage 21VDC Contact Form 6PST (4 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features Mounting Type Through Hole	Coil Type	Non Latching
Contact Form 6PST (4 Form A, 2 Form B) Contact Rating (Current) 6A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Coil Current	32mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Coil Voltage	21VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Contact Form	6PST (4 Form A, 2 Form B)
Turn On Voltage (Max) 15.8 VDC Turn Off Voltage (Min) 3.2 VDC Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Contact Rating (Current)	6A
Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Switching Voltage	250VAC, 30VDC - Max
Operate Time 20ms Release Time 10ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	15.8 VDC
Release Time 10ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	3.2 VDC
Features - Mounting Type Through Hole	Operate Time	20ms
Mounting Type Through Hole	Release Time	10ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
101111	Termination Style	PC Pin
Report errors?		Report errors?

SFY4-DC21V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SFY4-DC21V Payment Methods



















SFY4-DC21V Shipping Methods













If you have any question about SFY4-DC21V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com