



SG-8002CE-STB Information



For Reference Only

Part Number SG-8002CE-STB

Manufacturer EPSON

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG TTL 5V STBY 50PPM SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SG-8002CE-STB Specifications

Manufacturer Part Number Manufacturer EPSON Category Crystals, Oscillators, Resonators Programmable Oscillators Package 4-SMD, No Lead Series SG-8002 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 125MHz Function Standby Output Voltage - Supply Frequency Stability Frequency Stability Frequency Stability (Total) Operation Temperature
Category Crystals, Oscillators, Resonators Programmable Oscillators Package 4-SMD, No Lead Series SG-8002 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 125MHz Function Standby Output TTL Voltage - Supply Frequency Stability Frequency Stability (Total)
Package 4-SMD, No Lead Series SG-8002 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output TTL Voltage - Supply 5V Frequency Stability + ±50ppm Frequency Stability (Total)
Package 4-SMD, No Lead Series SG-8002 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output TTL Voltage - Supply 5V Frequency Stability + ±50ppm Frequency Stability (Total)
SeriesSG-8002TypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 125MHzFunctionStandbyOutputTTLVoltage - Supply5VFrequency Stability±50ppmFrequency Stability (Total)-
Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output TTL Voltage - Supply 5V Frequency Stability + ±50ppm Frequency Stability (Total) -
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 125MHz Function Standby Output TTL Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) -
Available Frequency Range Function Standby Output TTL Voltage - Supply Frequency Stability Frequency Stability (Total) TTL TTL TTL TTL TTL TTL TTL T
Function Standby Output TTL Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) -
Output TTL Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) -
Voltage - Supply 5V Frequency Stability ±50ppm Frequency Stability (Total) -
Frequency Stability ±50ppm Frequency Stability (Total) -
Frequency Stability (Total) -
200C 700C
Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
Spread Spectrum Bandwidth -
Current - Supply (Max) 40mA
Ratings -
Mounting Type Surface Mount
Package / Case 4-SMD, No Lead
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)
Height 0.041" (1.05mm)
Report errors

SG-8002CE-STB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SG-8002CE-STB Payment Methods



















SG-8002CE-STB Shipping Methods













If you have any question about SG-8002CE-STB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com