

SG3100E-10SL-56P

SG3100E-10SL-56P Information

Heisener.com	 SG3100E-10SL-56P Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN RCPT 2POS WALL MNT PIN - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SG3100E-10SL-56P Specifications

ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-56Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishStrain ReliefVoltage - Rated-Voltage - Rated-		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-56Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishStrain ReliefVoltage - Rated-Current Rating-Current Rating-Curr	Manufacturer Part Number	SG3100E-10SL-56P
Circular ConnectorsPackage-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-56Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesStrain ReliefVoltage - Rated-Current Rating-Current Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - InsertIOSL-56Shell Size, MIL-Mouting TypePanel Mount, FlangeMounting TypeSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesSilverVoltage - RatedStrain ReliefVoltage - Rated-Current Rating-Strain Relief-Strain Relief- <t< td=""><td>Category</td><td>Connectors, Interconnects</td></t<>	Category	Connectors, Interconnects
SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-56Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage Rated-Current Rating-Current Rat		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert10SL-56Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesSilverVoltage - Rated-Current Rating-Current Rating- </td <td>Package</td> <td>-</td>	Package	-
Number of Positions2Shell Size - Insert10SL-56Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Series	SG, MIL-5015 Derivative
Shell Size - InsertIOSL-56Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Connector Type	Receptacle, Male Pins
Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesSrain ReliefVoltage - Rated-Current Rating-Shell Material, Finish-State State	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Shell Size - Insert	10SL-56
TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Mounting Type	Panel Mount, Flange
OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Termination	Solder Cup
Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Orientation	N (Normal)
Contact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Ingress Protection	Environment Resistant
FeaturesStrain ReliefVoltage - Rated-Current Rating-Outrent Rating-	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated-Current Rating-	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	-
Report errors?	Current Rating	-
		Report errors?

SG3100E-10SL-56P Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SG3100E-10SL-56P Payment Methods



SG3100E-10SL-56P Shipping Methods



If you have any question about SG3100E-10SL-56P, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com