



SG3100E-28-68S Information

Heisener.com

Part Number SG3100E-28-68S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN RCPT 35POS WALL MNT SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SG3100E-28-68S Specifications

Manufacturer Part NumberSG3100E-28-68SManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions35Shell Size - Insert28-68Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-Equivalent Agency-Report errors?	505100L-20-005 Specifications	
CategoryConnectors, InterconnectsPackage-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions35Shell Size - Insert28-68Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Manufacturer Part Number	SG3100E-28-68S
Package-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions35Shell Size - Insert28-68Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions35Shell Size - Insert28-68Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Category	Connectors, Interconnects
SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions35Shell Size - Insert28-68Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions35Shell Size - Insert28-68Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Package	-
Number of Positions35Shell Size - Insert28-68Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Series	SG, MIL-5015 Derivative
Shell Size - Insert 28-68 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated - Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated - Current Rating -	Number of Positions	35
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Shell Size - Insert	28-68
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated - Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated - Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated - Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Strain Relief Voltage - Rated Current Rating	Orientation	N (Normal)
Contact Finish Features Strain Relief Voltage - Rated Current Rating	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated - Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	-
Report errors?	Current Rating	-
		Report errors?

SG3100E-28-68S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SG3100E-28-68S Payment Methods



















SG3100E-28-68S Shipping Methods













If you have any question about SG3100E-28-68S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com