

SG3102E-24-59S Information

Heisener.com

Part Number SG3102E-24-59S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 14POS BOX MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SG3102E-24-59S Specifications

Manufacturer Part Number SG3102E-24-59S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Circular Connectors Package - Series SG, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 24-59 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series SG, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 24-59 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer Part Number	SG3102E-24-59S
Circular Connectors Package - Series SG, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 24-59 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - Series SG, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 24-59 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
Series SG, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert 24-59 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert24-59Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 24-59 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating	Series	SG, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	14
Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size - Insert	24-59
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating - Silver	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

SG3102E-24-59S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SG3102E-24-59S Payment Methods



















SG3102E-24-59S Shipping Methods













If you have any question about SG3102E-24-59S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com