



SG3102E-24-79P Information

Heisener.com

Part Number SG3102E-24-79P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 5POS BOX MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SG3102E-24-79P Specifications

| Manufacturer Part NumberSG3102E-24-79PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert24-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-Report errors? | | |
|--|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert24-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Manufacturer Part Number | SG3102E-24-79P |
| Package-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert24-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Manufacturer | Amphenol Industrial Operations |
| Package-SeriesSG, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert24-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Category | Connectors, Interconnects |
| Series SG, MIL-5015 Derivative Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-79 Shell Size, MIL | | Circular Connectors |
| Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert24-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Package | - |
| Number of Positions5Shell Size - Insert24-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Series | SG, MIL-5015 Derivative |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Number of Positions | 5 |
| Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating- | Shell Size - Insert | 24-79 |
| Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Shell Size, MIL | - |
| Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Mounting Type | Panel Mount, Flange |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Termination | Solder Cup |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - Current Rating | Orientation | N (Normal) |
| Contact Finish Silver Features - Voltage - Rated Current Rating - Silver - | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated 500VAC, 700VDC Current Rating - | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 500VAC, 700VDC Current Rating - | Contact Finish | Silver |
| Current Rating - | Features | - |
| - | Voltage - Rated | 500VAC, 700VDC |
| Report errors? | Current Rating | - |
| | | Report errors? |

SG3102E-24-79P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SG3102E-24-79P Payment Methods



















SG3102E-24-79P Shipping Methods













If you have any question about SG3102E-24-79P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com