



SG3106E-22-63P(SR) Information

Heisener.com

Part Number SG3106E-22-63P(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 12POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SG3106E-22-63P(SR) Specifications

Manufacturer Part Number \$G3106E-22-63P(\$R) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series \$G, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 12 Shell Size - Insert 22-63 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -		
CategoryConnectors, InterconnectsPackage-SeriesSG, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions12Shell Size - Insert22-63Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	SG3106E-22-63P(SR)
Package-SeriesSG, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions12Shell Size - Insert22-63Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package Scries SG, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 12 Shell Size - Insert 22-63 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Category	Connectors, Interconnects
Series SG, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 12 Shell Size - Insert 22-63 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions12Shell Size - Insert22-63Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions12Shell Size - Insert22-63Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	SG, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating	Number of Positions	12
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	22-63
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Strain Relief	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

SG3106E-22-63P(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SG3106E-22-63P(SR) Payment Methods



















SG3106E-22-63P(SR) Shipping Methods













If you have any question about SG3106E-22-63P(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com