



### SG3106E-32-76P(SR) Information

Heisener.com

Part Number SG3106E-32-76P(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

**Description** CONN PLUG 19POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SG3106E-32-76P(SR) Specifications

Manufacturer Part Number       SG3106E-32-76P(SR)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       SG, MIL-5015 Derivative         Connector Type       Plug, Male Pins         Number of Positions       19         Shell Size - Insert       32-76         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       500VAC, 700VDC         Current Rating       -         Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series SG, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 19 Shell Size - Insert 32-76 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating -	Manufacturer Part Number	SG3106E-32-76P(SR)
Circular Connectors  Package - Series SG, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 19 Shell Size - Insert 32-76 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - Series SG, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 19 Shell Size - Insert 32-76 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
Series SG, MIL-5015 Derivative  Connector Type Plug, Male Pins  Number of Positions 19  Shell Size - Insert 32-76  Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions19Shell Size - Insert32-76Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  32-76  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating  -	Series	SG, MIL-5015 Derivative
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating  -	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating	Number of Positions	19
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Shell Size - Insert	32-76
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Strain Relief	Orientation	N (Normal)
Contact Finish Silver  Features Strain Relief Voltage - Rated 500VAC, 700VDC  Current Rating -	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

### SG3106E-32-76P(SR) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SG3106E-32-76P(SR) Payment Methods



















# SG3106E-32-76P(SR) Shipping Methods













If you have any question about SG3106E-32-76P(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com