



SG3106E-36-77P(SR) Information

Heisener.com

Part Number SG3106E-36-77P(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 7POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SG3106E-36-77P(SR) Specifications

Manufacturer Part Number \$G3106E-36-77P(\$R) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series \$G, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert 36-77 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -		
CategoryConnectors, InterconnectsPackage-SeriesSG, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert36-77Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	SG3106E-36-77P(SR)
Package-SeriesSG, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert36-77Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesSG, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert36-77Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesSG, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert36-77Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900 VAC, 1250 VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert36-77Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions7Shell Size - Insert36-77Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Series	SG, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating	Number of Positions	7
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	36-77
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Strain Relief	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	900VAC, 1250VDC
D	Current Rating	-
Report errors?		Report errors?

SG3106E-36-77P(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SG3106E-36-77P(SR) Payment Methods



















SG3106E-36-77P(SR) Shipping Methods













If you have any question about SG3106E-36-77P(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com