



### SG3106E-40-53P Information

Heisener.com

Part Number SG3106E-40-53P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 60POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SG3106E-40-53P Specifications

Manufacturer Part Number       SG3106E-40-53P         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       SG, MIL-5015 Derivative         Connector Type       Plug, Male Pins         Number of Positions       60         Shell Size - Insert       40-53         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       500VAC, 700VDC         Current Rating       -         Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series SG, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 60 Shell Size - Insert 40-53 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating -	Manufacturer Part Number	SG3106E-40-53P
Circular Connectors  Package - Series SG, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 60 Shell Size - Insert 40-53 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - Series SG, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 60 Shell Size - Insert 40-53 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
Series SG, MIL-5015 Derivative  Connector Type Plug, Male Pins  Number of Positions 60  Shell Size - Insert 40-53  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -		Circular Connectors
Connector Type Plug, Male Pins  Number of Positions 60  Shell Size - Insert 40-53  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Package	-
Number of Positions Shell Size - Insert 40-53 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Series	SG, MIL-5015 Derivative
Shell Size - Insert 40-53  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	60
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Shell Size - Insert	40-53
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating	Orientation	N (Normal)
Contact Finish Silver  Features Strain Relief Voltage - Rated 500VAC, 700VDC  Current Rating -	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

#### SG3106E-40-53P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SG3106E-40-53P Payment Methods



















## SG3106E-40-53P Shipping Methods













If you have any question about SG3106E-40-53P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com