

SG3108E-36-6S(SR)

SG3108E-36-6S(SR) Information

Heisener.com	SG3108E-36-6S(SR) Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN PLUG 6POS INLINE SKT RA - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SG3108E-36-6S(SR) Specifications

Manufacturer Part Number SG3108E-36-6S(SR) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Package - Series SG, MIL-5015 Derivative Ponector Type Plug, Female Sockets Number of Positions 6 Shell Size Insert 36-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Partiation Solder Cup Orientation N(Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Voltage - Rated Stora Relief Voltage - Rated Stora Relief		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesSG, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesSioVAC, 700VDCVoltage - Rated.Current Rating.	Manufacturer Part Number	SG3108E-36-6S(SR)
Circular ConnectorsPackage-SeriesSG, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated.Current Rating.	Manufacturer	Amphenol Industrial Operations
Package-SeriesSG, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesSG, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Package	-
Number of Positions6Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	SG, MIL-5015 Derivative
Shell Size - Insert36-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSitverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Number of Positions	6
Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	36-6
TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Mounting Type	Free Hanging (In-Line), Right Angle
OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Termination	Solder Cup
Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Orientation	N (Normal)
Contact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Ingress Protection	Environment Resistant
FeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated500VAC, 700VDCCurrent Rating-	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	500VAC, 700VDC
Report error	Current Rating	-
1		Report errors?

SG3108E-36-6S(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SG3108E-36-6S(SR) Payment Methods





If you have any question about SG3108E-36-6S(SR), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com