



SHP1000PS28 Information



For Reference Only

Part Number SHP1000PS28
Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 28V 1000W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SHP1000PS28 Specifications

Manufacturer Part Number SHP1000PS28 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 43A Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 43A Power (Watts) 1000W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Manufacturer Part Number	SHP1000PS28
Package - Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 43A Power (Watts) 1000W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Manufacturer	XP Power
Package - Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 43A Power (Watts) 1000W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 43A Power (Watts) 1000W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)		AC DC Converters
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)43APower (Watts)1000WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 43A Power (Watts) 1000W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Series	SHP
Voltage - Input 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 85 ~ 264 VAC 28V 1000 1000 -40°C ~ 70°C (With Derating) Power (Watts) Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Type	Enclosed
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Sty (3000V) Efficiency Operating Temperature Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Size / Dimension 28V Current - Output (Max) - 43A - Current - Output (Max) 43A Power (Watts) 1000W Applications ITE (Commercial) 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Voltage - Isolation Voltage - Isolation Size / Dimension - Current - Output (Max) - A3A - 1000W APPlications ITE (Commercial) 3kV (3000V) Size / Dimension - Chassis Mount Size / Dimension - Current - Output (Max) - A3A - Current - Output (Max) - A3A - Current - Output (Max) - A3A - Current - Output (Max) - A3A - Commercial) Six (3000V) - Size / Dimension - Chassis Mount Size / Dimension - Chassi	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Size / Dimension - 40°C ~ 70°C (With Derating) Chassis Mount Size / Dimension - Output (Max) - Current - Output (Max) - A3A - Current - Output (Max) - A3A - Current - Output (Max) - Inout (Max) - Commercial) - Commercial	Voltage - Output 1	28V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Voltage - Output 2	-
Current - Output (Max) 43A Power (Watts) 1000W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Current - Output (Max)	43A
Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Power (Watts)	1000W
Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Applications	ITE (Commercial)
Operating Temperature -40°C ~ 70°C (With Derating) Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Efficiency	85%
Mounting Type Chassis Mount Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Operating Temperature	-40°C ~ 70 °C (With Derating)
Size / Dimension 9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)	Features	Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	9.55" L x 5.90" W x 2.40" H (242.6mm x 149.8mm x 61.0mm)
		Report errors?

SHP1000PS28 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SHP1000PS28 Payment Methods





















SHP1000PS28 Shipping Methods













If you have any question about SHP1000PS28, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com