



SHP650PS48-EF Information

w.helsener.com

For Reference Only

Part Number SHP650PS48-EF

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 650W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SHP650PS48-EF Specifications

Manufacturer Part Number Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package Series SHP Type Enclosed Number of Outputs Voltage - Input Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications Voltage - Isolation ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.5A Power (Watts) 650W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)	Manufacturer Part Number	SHP650PS48-EF
AC DC Converters Package - Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.5A Power (Watts) 650W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)	Manufacturer	XP Power
Package - Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.5A Power (Watts) 650W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)	Category	Power Supplies - External/Internal (Off-Board)
Series SHP Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.5A Power (Watts) 650W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.5A Power (Watts) 650W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.5A Power (Watts) 650W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)	Series	SHP
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13.5A Power (Watts) 650W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)	Type	Enclosed
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Style	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -40°C ~ 70°C (With Derating)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -40°C ~ 70°C (With Derating)	Voltage - Output 2	-
Current - Output (Max) 13.5A Power (Watts) 650W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature -40°C ~ 70°C (With Derating)	Voltage - Output 3	-
Power (Watts) $650W$ ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 85% Operating Temperature $-40^{\circ}C \sim 70^{\circ}C$ (With Derating)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV$ (3000V)Efficiency 85% Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Current - Output (Max)	13.5A
Voltage - Isolation $3kV (3000V)$ Efficiency 85% Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Power (Watts)	650W
Efficiency 85% Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Applications	ITE (Commercial)
Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Voltage - Isolation	3kV (3000V)
	Efficiency	85%
Features Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input	Operating Temperature	$-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
	Features	Adjustable Output, Load Sharing, Remote On/Off, Standby Output, Universal Input
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Size / Dimension 9.18" L x 4.00" W x 2.50" H (233.2mm x 101.6mm x 63.5mm)	Size / Dimension	9.18" L x 4.00" W x 2.50" H (233.2mm x 101.6mm x 63.5mm)
Report er		Report errors?

SHP650PS48-EF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SHP650PS48-EF Payment Methods



















SHP650PS48-EF Shipping Methods













If you have any question about SHP650PS48-EF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com