



SI8234BD-D-ISR Information



For Reference Only

Part Number SI8234BD-D-ISR **Manufacturer** Silicon Labs

Category Isolators

Isolators - Gate Drivers

Description DGTL ISO 5KV 2CH GATE DVR 16SOIC

Package 16-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SI8234BD-D-ISR Specifications

Manufacturer Part Number Si8234BD-D-ISR Manufacturer Silicon Labs Category Isolators Package 16-SOIC (0.295", 7.50mm Width) Series Automotive, AEC-Q100 Technology Capacitive Coupling Number of Channels 2 Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 20kV/μs Propagation Delay tpLH / tpHL (Max) 60ns, 60ns Pulse Width Distortion (Max) 5.6ns Rise / Fall Time (Typ) 12ns, 12ns (Max) Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) 9.4 V ~ 24 V Operating Temperature 40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC (0.295", 7.50mm Width)		
Category Isolators Package 16-SOIC (0.295", 7.50mm Width) Series Automotive, AEC-Q100 Technology Capacitive Coupling Number of Channels 2 Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 20kV/μs Propagation Delay tpLH / tpHL (Max) 60ns, 60ns Pulse Width Distortion (Max) 5.6ns Rise / Fall Time (Typ) 12ns, 12ns (Max) Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 9.4 V ~ 24 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Manufacturer Part Number	SI8234BD-D-ISR
Isolators - Gate Drivers	Manufacturer	Silicon Labs
Package 16-SOIC (0.295", 7.50mm Width) Series Automotive, AEC-Q100 Technology Capacitive Coupling Number of Channels 2 Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 20kV/μs Propagation Delay tpLH / tpHL (Max) 60ns, 60ns Pulse Width Distortion (Max) 5.6ns Rise / Fall Time (Typ) 12ns, 12ns (Max) Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) 9.4 V ~ 24 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Category	Isolators
Series Automotive, AEC-Q100 Technology Capacitive Coupling Number of Channels 2 Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 20kV/µs Propagation Delay tpLH / tpHL (Max) 60ns, 60ns Pulse Width Distortion (Max) 5.6ns Rise / Fall Time (Typ) 12ns, 12ns (Max) Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 9.4 V ~ 24 V Operating Temperature 40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)		Isolators - Gate Drivers
TechnologyCapacitive CouplingNumber of Channels2Voltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)20kV/μsPropagation Delay tpLH / tpHL (Max)60ns, 60nsPulse Width Distortion (Max)5.6nsRise / Fall Time (Typ)12ns, 12ns (Max)Current - Output High, Low2A, 4ACurrent - Peak Output4AVoltage - Forward (Vf) (Typ)-Current - DC Forward (If) (Max)-Voltage - Supply9.4 V ~ 24 VOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case16-SOIC (0.295", 7.50mm Width)	Package	16-SOIC (0.295", 7.50mm Width)
Number of Channels2Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) $20k \text{V}/\mu \text{s}$ Propagation Delay tpLH / tpHL (Max) $60ns$, $60ns$ Pulse Width Distortion (Max) $5.6ns$ Rise / Fall Time (Typ) $12ns$, $12ns$ (Max)Current - Output High, Low $2A$, $4A$ Current - Peak Output $4A$ Voltage - Forward (Vf) (Typ)-Current - DC Forward (If) (Max)-Voltage - Supply $9.4 \text{ V} \sim 24 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case 16-SOIC (0.295", 7.50mm Width)	Series	Automotive, AEC-Q100
Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 20kV/ μ s Propagation Delay tpLH / tpHL (Max) 60ns, 60ns Pulse Width Distortion (Max) 5.6ns Rise / Fall Time (Typ) 12ns, 12ns (Max) Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 9.4 V ~ 24 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Technology	Capacitive Coupling
Common Mode Transient Immunity (Min) Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) Current - Output High, Low Current - Peak Output Voltage - Forward (Vf) (Typ) Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 20kV/µs 60ns, 60ns 5.6ns 12ns, 12ns (Max) 2A, 4A 4A	Number of Channels	2
Propagation Delay tpLH / tpHL (Max) 60ns, 60ns Pulse Width Distortion (Max) 5.6ns Rise / Fall Time (Typ) 12ns, 12ns (Max) Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) Voltage - Supply 9.4 V ~ 24 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Voltage - Isolation	5000Vrms
Pulse Width Distortion (Max) Rise / Fall Time (Typ) 12ns, 12ns (Max) Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature 40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Common Mode Transient Immunity (Min)	20kV/μs
Rise / Fall Time (Typ) Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) Voltage - Supply 9.4 V ~ 24 V Operating Temperature 40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Propagation Delay tpLH / tpHL (Max)	60ns, 60ns
Current - Output High, Low 2A, 4A Current - Peak Output 4A Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) Voltage - Supply 9.4 V ~ 24 V Operating Temperature 40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Pulse Width Distortion (Max)	5.6ns
Current - Peak Output Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) Voltage - Supply 9.4 V ~ 24 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Rise / Fall Time (Typ)	12ns, 12ns (Max)
Voltage - Forward (Vf) (Typ) - Current - DC Forward (If) (Max) - Voltage - Supply 9.4 V ~ 24 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Current - Output High, Low	2A, 4A
Current - DC Forward (If) (Max)-Voltage - Supply $9.4 \text{ V} \sim 24 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case 16-SOIC (0.295", 7.50mm Width)	Current - Peak Output	4A
Voltage - Supply 9.4 V \sim 24 V Operating Temperature -40°C \sim 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Voltage - Forward (Vf) (Typ)	-
Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Current - DC Forward (If) (Max)	-
Mounting Type Surface Mount Package / Case 16-SOIC (0.295", 7.50mm Width)	Voltage - Supply	9.4 V ~ 24 V
Package / Case 16-SOIC (0.295", 7.50mm Width)	Operating Temperature	-40°C ~ 125°C
	Mounting Type	Surface Mount
Supplier Device Package 16-SOIC	Package / Case	16-SOIC (0.295", 7.50mm Width)
	Supplier Device Package	16-SOIC
Approvals CQC, CSA, UR, VDE	Approvals	CQC, CSA, UR, VDE
Report errors?		Report errors?

SI8234BD-D-ISR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SI8234BD-D-ISR Payment Methods



















SI8234BD-D-ISR Shipping Methods













If you have any question about SI8234BD-D-ISR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com