



SI8384P-IUR Information

Heisener.com

For Reference Only

Part Number SI8384P-IUR
Manufacturer Silicon Labs
Category Isolators
Digital Isolators

Description DGTL ISO 2.5KV 8CH 20QSOP

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SI8384P-IUR Specifications

Manufacturer Part Number \$\$18384P-IUR Manufacturer \$\$1850ators Category Digital Isolators Package - Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 8 Inputs - Side 1/Side 2 8/0 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) - Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) - Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case - Supplier Device Package -		
Category Isolators Package - Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 8 Inputs - Side 1/Side 2 8/0 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) - Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) - Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case - Supplier Device Package -	Manufacturer Part Number	SI8384P-IUR
Package - Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 8 Inputs - Side 1/Side 2 8/0 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) - Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) - Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case - Supplier Device Package -	Manufacturer	Silicon Labs
Package - Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 8 Inputs - Side 1/Side 2 8/0 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) - Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) - Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case - Supplier Device Package -	Category	Isolators
Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 8 Inputs - Side 1/Side 2 8/0 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) - Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) - Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case - Supplier Device Package -		Digital Isolators
Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 8 Inputs - Side 1/Side 2 8/0 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) - Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) - Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case - Supplier Device Package -	Package	-
Type General Purpose Isolated Power No Number of Channels 8 Inputs - Side 1/Side 2 8/0 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) - Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) - Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case - Supplier Device Package -	Series	-
Isolated PowerNoNumber of Channels8Inputs - Side 1/Side 28/0Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)-Data Rate2MbpsPropagation Delay tpLH / tpHL (Max)-Pulse Width Distortion (Max)-Rise / Fall Time (Typ)3.9ns, 3.7nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Technology	Capacitive Coupling
Number of Channels8Inputs - Side 1/Side 28/0Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)-Data Rate2MbpsPropagation Delay tpLH / tpHL (Max)-Pulse Width Distortion (Max)-Rise / Fall Time (Typ)3.9ns, 3.7nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Type	General Purpose
Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation Common Mode Transient Immunity (Min) Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - Sundant And Common Mode Transient Immunity (Min) - Ribidity Common Mode Transient Immunity (Min) - 2Mbps - 2Mbps - 2Mbps - 2Mbps - 2Mbps - 2More — 40°C ~ 125°C - Supplier Device Package	Isolated Power	No
Channel Type Voltage - Isolation Common Mode Transient Immunity (Min) Data Rate Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) Voltage - Supply Operating Temperature Package / Case Supplier Device Package Unidirectional 2500Vrms - Cambon 300 - 300 - 300 - 300 - 300 - 300 - 400° C ~ 125° C - 500	Number of Channels	8
Voltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)-Data Rate2MbpsPropagation Delay tpLH / tpHL (Max)-Pulse Width Distortion (Max)-Rise / Fall Time (Typ)3.9ns, 3.7nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Inputs - Side 1/Side 2	8/0
Common Mode Transient Immunity (Min) Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature Package / Case Supplier Device Package - - - - - - - - - - - - -	Channel Type	Unidirectional
Data Rate 2Mbps Propagation Delay tpLH / tpHL (Max) - Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case - Supplier Device Package -	Voltage - Isolation	2500Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) Voltage - Supply Operating Temperature Package / Case Supplier Device Package	Common Mode Transient Immunity (Min)	-
Pulse Width Distortion (Max) Rise / Fall Time (Typ) 3.9ns, 3.7ns Voltage - Supply 2.25 V ~ 5.5 V Operating Temperature Package / Case Supplier Device Package - - - - - - - - - - - - -	Data Rate	2Mbps
Rise / Fall Time (Typ) $3.9 \text{ns}, 3.7 \text{ns}$ Voltage - Supply $2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case-Supplier Device Package-	Propagation Delay tpLH / tpHL (Max)	-
Voltage - Supply $2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case-Supplier Device Package-	Pulse Width Distortion (Max)	-
Operating Temperature -40°C ~ 125°C Package / Case - Supplier Device Package -	Rise / Fall Time (Typ)	3.9ns, 3.7ns
Package / Case - Supplier Device Package -	Voltage - Supply	2.25 V ~ 5.5 V
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

SI8384P-IUR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SI8384P-IUR Payment Methods



















SI8384P-IUR Shipping Methods













If you have any question about SI8384P-IUR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com