



SI8463BB-B-IS1R Information



For Reference Only

Part Number SI8463BB-B-IS1R

ManufacturerSilicon LabsCategoryIsolators

Digital Isolators

Description DGTL ISO 2.5KV GEN PURP 16SOIC **Package** 16-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SI8463BB-B-IS1R Specifications

Manufacturer Part Number \$18463BB-B\sir Manufacturer \$1100 Labs Category Isolators Package 16-SOIC (0.154", 3.90mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 6 Inputs - Side 1/Side 2 3/3 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25xV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 9.5ns, 9.5ns Pulse Width Distortion (Max) 2.5ns Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC (0.154", 3.90mm Width)		
Category Isolators Package 16-SOIC (0.154", 3.90mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 6 Inputs - Side 1/Side 2 3/3 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 9.5ns, 9.5ns Pulse Width Distortion (Max) 2.5ns Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Manufacturer Part Number	SI8463BB-B-IS1R
Package Digital Isolators Package 16-SOIC (0.154", 3.90mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 6 Inputs - Side 1/Side 2 3/3 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/μs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 9.5ns, 9.5ns Pulse Width Distortion (Max) 2.5ns Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Manufacturer	Silicon Labs
Package 16-SOIC (0.154", 3.90mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 6 Inputs - Side 1/Side 2 3/3 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/μs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 9.5ns, 9.5ns Pulse Width Distortion (Max) 2.5ns Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Category	Isolators
Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 6 Inputs - Side 1/Side 2 3/3 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 9.5ns, 9.5ns Pulse Width Distortion (Max) 2.5ns Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC		Digital Isolators
TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels6Inputs - Side 1/Side 23/3Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/μs (Typ)Data Rate150MbpsPropagation Delay tpLH / tpHL (Max)9.5ns, 9.5nsPulse Width Distortion (Max)2.5nsRise / Fall Time (Typ)3.8ns, 2.8nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Package	16-SOIC (0.154", 3.90mm Width)
Type General Purpose Isolated Power No Number of Channels 6 Inputs - Side 1/Side 2 3/3 Channel Type Unidirectional Voltage - Isolation 2500 Vrms Common Mode Transient Immunity (Min) 25kV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 9.5ns, 9.5ns Pulse Width Distortion (Max) 2.5ns Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Series	-
Isolated Power Number of Channels Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Technology	Capacitive Coupling
Number of Channels6Inputs - Side 1/Side 23/3Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/μs (Typ)Data Rate150MbpsPropagation Delay tpLH / tpHL (Max)9.5ns, 9.5nsPulse Width Distortion (Max)2.5nsRise / Fall Time (Typ)3.8ns, 2.8nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Type	General Purpose
Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Isolated Power	No
Channel Type Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Channels	6
Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/ μ s (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 9.5ns, 9.5ns Pulse Width Distortion (Max) 2.5ns Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Inputs - Side 1/Side 2	3/3
Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Unidirectional
Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 9.5ns, 9.5ns Pulse Width Distortion (Max) 2.5ns Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Voltage - Isolation	2500Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Common Mode Transient Immunity (Min)	25kV/μs (Typ)
Pulse Width Distortion (Max) Rise / Fall Time (Typ) 3.8ns, 2.8ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Data Rate	150Mbps
Rise / Fall Time (Typ) $3.8 \text{ns}, 2.8 \text{ns}$ Voltage - Supply $2.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 16-SOIC (0.154° , 3.90mm Width)Supplier Device Package 16-SOIC	Propagation Delay tpLH / tpHL (Max)	9.5ns, 9.5ns
Voltage - Supply $2.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $16\text{-SOIC } (0.154^{\circ}\text{H}, 3.90 \text{mm Width})$ Supplier Device Package 16-SOIC	Pulse Width Distortion (Max)	2.5ns
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Rise / Fall Time (Typ)	3.8ns, 2.8ns
Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Voltage - Supply	2.7 V ~ 5.5 V
Supplier Device Package 16-SOIC	Operating Temperature	-40°C ~ 125°C
	Package / Case	16-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	16-SOIC
		Report errors?

SI8463BB-B-IS1R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SI8463BB-B-IS1R Payment Methods



















SI8463BB-B-IS1R Shipping Methods













If you have any question about SI8463BB-B-IS1R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com