

SI8661EC-B-IS1

SI8661EC-B-IS1 Information



For Reference Only

rt Number	SI8661EC-B-IS1
nufacturer	Silicon Labs
tegory	Isolators Digital Isolators
scription	DGTL ISO 3.75KV GEN PURP 16SOIC
ckage	16-SOIC (0.154", 3.90mm Width)
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SI8661EC-B-IS1 Specifications

Manufacturer Part Number S18661EC-B-1S1 Manufacturer Silicon Labs Category Isolators Digital Isolators Digital Isolators Package 16-SOIC (0.154", 3.90mm Width) Series Automotive, AEC-Q100 Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 6 Inputs - Side 1/Side 2 5/1 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 35kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 4.5ns Rise / Fall Time (Typ) 2.5 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC		
CategoryIsolatorsDigital IsolatorsPackage16-SOIC (0.154", 3.90mm Width)SeriesAutomotive, AEC-Q100TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels6Inputs - Side 1/Side 25/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5 v ~ 5.5 VOperating Temperature440°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	SI8661EC-B-IS1
Digital IsolatorsPackage16-SOIC (0.154", 3.90mm Width)SeriesAutomotive, AEC-Q100TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels6Inputs - Side 1/Side 25/1Channel TypeUnidirectionalVoltage - Isolation358V/µsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)	Manufacturer	Silicon Labs
Package16-SOIC (0.154", 3.90mm Width)SeriesAutomotive, AEC-Q100TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels6Inputs - Side 1/Side 25/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsNotage - Supply2.5 V ~ 5.5 VOperating Temperature40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)	Category	Isolators
SeriesAutomotive, AEC-Q100TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels6Inputs - Side 1/Side 25/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsKise / Fall Time (Typ)2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC		Digital Isolators
TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels6Inputs - Side 1/Side 25/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Package	16-SOIC (0.154", 3.90mm Width)
TypeGeneral PurposeIsolated PowerNoNumber of Channels6Inputs - Side 1/Side 2S/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)SikV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPuse Width Distortion (Max)2.5 x - 5.5 VNotage - Supply.25 V ~ 5.5 VOperating Temperature4.0°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)	Series	Automotive, AEC-Q100
Isolated PowerNoNumber of Channels6Inputs - Side 1/Side 25/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5 N < 5.5 V	Technology	Capacitive Coupling
Number of Channels6Inputs - Side 1/Side 25/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Туре	General Purpose
Inputs - Side 1/Side 25/1Inputs - Side 1/Side 25/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Isolated Power	No
IIChannel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5 Ns, 2.5 nsVoltage - Supply2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)	Number of Channels	6
Voltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5 Ns, 2.5nsVoltage - Supply2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Inputs - Side 1/Side 2	5/1
Common Mode Transient Immunity (Min)35kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Channel Type	Unidirectional
Data Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Voltage - Isolation	3750Vrms
Propagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Common Mode Transient Immunity (Min)	35kV/µs
Pulse Width Distortion (Max)4.5nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Data Rate	150Mbps
Rise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Propagation Delay tpLH / tpHL (Max)	13ns, 13ns
Voltage - Supply2.5 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Pulse Width Distortion (Max)	4.5ns
Operating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Voltage - Supply	2.5 V ~ 5.5 V
Supplier Device Package 16-SOIC	Operating Temperature	-40°C ~ 125°C
	Package / Case	16-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	16-SOIC
		Report errors?

SI8661EC-B-IS1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SI8661EC-B-IS1 Payment Methods



SI8661EC-B-IS1 Shipping Methods



If you have any question about SI8661EC-B-IS1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com