

Heisener.com

For Reference Only

SIP110-PPEC-D15-SK-BK

SIP110-PPEC-D15-SK-BK Information

Part NumberSIP110-PPEC-D15-SK-BKManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Board In, Direct Wire to

Board

Description CONN PLUG IDC .100" 30POS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIP110-PPEC-D15-SK-BK Specifications

Manufacturer Part Number SIP110-PPEC-D15-SK-BK Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Rectangular Connectors - Board In, Direct Wire to Board Package - Series - Connector Type Ribbon Cable, DIP Header Number of Positions 30 Cable Pitch 0.050" (1.27mm) Board-Side Pitch 0.100" (2.54mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Mounting Type Through Hole, Kinked Pin Cable Termination IDC Wire Gauge 28 AWG Features Cover Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Color Black		
Category Connectors, Interconnects Rectangular Connectors - Board In, Direct Wire to Board Package - Series - Connector Type Ribbon Cable, DIP Header Number of Positions 30 Cable Pitch 0.050" (1.27mm) Board-Side Pitch 0.100" (2.54mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Mounting Type Through Hole, Kinked Pin Cable Termination IDC Wire Gauge 28 AWG Features Cover Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Color	Manufacturer Part Number	SIP110-PPEC-D15-SK-BK
Rectangular Connectors - Board In, Direct Wire to Board Package - Series - Connector Type Ribbon Cable, DIP Header Number of Positions 30 Cable Pitch 0.050" (1.27mm) Board-Side Pitch 0.100" (2.54mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Mounting Type Through Hole, Kinked Pin Cable Termination IDC Wire Gauge 28 AWG Features Cover Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Color Black	Manufacturer	Sullins Connector Solutions
Package - Series - Connector Type Ribbon Cable, DIP Header Number of Positions 30 Cable Pitch 0.050" (1.27mm) Board-Side Pitch 0.100" (2.54mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Mounting Type Through Hole, Kinked Pin Cable Termination IDC Wire Gauge 28 AWG Features Cover Contact Finish Tin Contact Finish Thickness 100μin (2.54μm) Color Black	Category	Connectors, Interconnects
Series - Connector Type Ribbon Cable, DIP Header Number of Positions 30 Cable Pitch 0.050" (1.27mm) Board-Side Pitch 0.100" (2.54mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Mounting Type Through Hole, Kinked Pin Cable Termination IDC Wire Gauge 28 AWG Features Cover Contact Finish Tin Contact Finish Thickness 100μin (2.54μm) Color Black		Rectangular Connectors - Board In, Direct Wire to Board
Connector TypeRibbon Cable, DIP HeaderNumber of Positions30Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Package	-
Number of Positions 30 Cable Pitch 0.050" (1.27mm) Board-Side Pitch 0.100" (2.54mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Mounting Type Through Hole, Kinked Pin Cable Termination IDC Wire Gauge 28 AWG Features Cover Contact Finish Tin Contact Finish Thickness 100μin (2.54μm) Color Black	Series	-
Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Connector Type	Ribbon Cable, DIP Header
Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Number of Positions	30
Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Cable Pitch	0.050" (1.27mm)
Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Board-Side Pitch	0.100" (2.54mm)
Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Number of Rows	2
Cable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Row Spacing	0.100" (2.54mm)
Wire Gauge28 AWGFeaturesCoverContact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Mounting Type	Through Hole, Kinked Pin
Features Cover Contact Finish Contact Finish Thickness 100µin (2.54µm) Color Black	Cable Termination	IDC
Contact FinishTinContact Finish Thickness100μin (2.54μm)ColorBlack	Wire Gauge	28 AWG
Contact Finish Thickness 100μin (2.54μm) Color Black	Features	Cover
Color Black	Contact Finish	Tin
	Contact Finish Thickness	100μin (2.54μm)
Report errors?	Color	Black
		Report errors?

SIP110-PPEC-D15-SK-BK Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIP110-PPEC-D15-SK-BK Payment Methods



















SIP110-PPEC-D15-SK-BK Shipping Methods













If you have any question about SIP110-PPEC-D15-SK-BK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com