

SIP110-PPKC-D07-SK-BK

SIP110-PPKC-D07-SK-BK Information

Description Package	CONN PLUG IDC .100" 14POS -	
	For the pricing/inventory/lead time, please contact us	Request a Quote
	-	Package - For the pricing/inventory/lead time, please contact

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SIP110-PPKC-D07-SK-BK Specifications

Manufacturer Part NumberSIP110-PPKC-D07-SK-BKManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Series-Connector TypeRibbon Cable, DIP HeaderNumber of Positions14Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGContext FinishGoldContext Finish Thickness15µin (0.38µm)Context Finish Thickness15µin (0.38µm)		
CategoryConnectors, Interconnects Rectangular Connectors - Board In, Direct Wire to BoardPackage-Series-Connector TypeRibbon Cable, DIP HeaderNumber of Positions14Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Manufacturer Part Number	SIP110-PPKC-D07-SK-BK
Rectangular Connectors - Board In, Direct Wire to BoardPackage-Series-Connector TypeRibbon Cable, DIP HeaderNumber of Positions14Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Manufacturer	Sullins Connector Solutions
Package-Series-Connector TypeRibbon Cable, DIP HeaderNumber of Positions14Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Category	Connectors, Interconnects
Series-Connector TypeRibbon Cable, DIP HeaderNumber of Positions14Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack		Rectangular Connectors - Board In, Direct Wire to Board
Connector TypeRibbon Cable, DIP HeaderNumber of Positions14Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting Type0.100" (2.54mm)Cable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Package	-
Number of Positions14Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Series	-
Cable Pitch0.050" (1.27mm)Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Connector Type	Ribbon Cable, DIP Header
Board-Side Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Number of Positions	14
Number of Rows2Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Cable Pitch	0.050" (1.27mm)
Row Spacing0.100" (2.54mm)Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Board-Side Pitch	0.100" (2.54mm)
Mounting TypeThrough Hole, Kinked PinCable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Number of Rows	2
Cable TerminationIDCWire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Row Spacing	0.100" (2.54mm)
Wire Gauge28 AWGFeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Mounting Type	Through Hole, Kinked Pin
FeaturesCoverContact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Cable Termination	IDC
Contact FinishGoldContact Finish Thickness15µin (0.38µm)ColorBlack	Wire Gauge	28 AWG
Contact Finish Thickness15µin (0.38µm)ColorBlack	Features	Cover
Color Black	Contact Finish	Gold
	Contact Finish Thickness	15µin (0.38µm)
Peport errors	Color	Black
Report crisis		Report errors?

SIP110-PPKC-D07-SK-BK Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SIP110-PPKC-D07-SK-BK Payment Methods



If you have any question about SIP110-PPKC-D07-SK-BK, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com